(12)UK Patent (19)GB (11)2 400 126 (13)B

(45) Date of publication: 21.06.2006

(54) Title of the invention: Mono diameter wellbore casing

(51) INT CL: **E21B 43/10** (2006.01)

(21) Application No: **0412876.5**

(22) Date of Filing: **12.11.2002**

(30) Priority Data:
(31) **60339013** (32) **12.11.2001** (33) **US**
(31) **30338996** (32) **12.11.2001** (33) **US**
(31) **60363829** (32) **13.03.2002** (33) **US**
(31) **60387961** (32) **12.06.2002** (33) **US**

(60) Parent of Application No(s)
0509630.0, 0509631.8, 0509626.8, 0509618.5, 0509627.6, 0509629.2, 0509620.1 under Section 15(4) of the Patents Act 1977

(86) International Application Data:
PCT/US2002/036267 En 12.11.2002

(87) International Publication Data:
WO2003/042487 En 22.05.2003

(43) Date A Publication: **06.10.2004**

(52) UK CL (Edition X):
E1F FLA

(56) Documents Cited:
GB 2395734 A
EP 1555386 A1
WO 2002/053867 A2
US 5348095 A
US 3785193 A
GB 2380503 A
WO 2003/036018 A2
US 5957195 A
US 4168747 A

(58) Field of Search:
As for published application 2400126 A *viz:*
Other: **U.S. :**
166/121,182,202,207,212,216,217,242.
8,277,382,387
updated as appropriate

Additional Fields

(continued on next page)

(72) Inventor(s):
Lev Ring
David Paul Brisco
Brock Wayne Watson
Kevin Karl Waddell

(73) Proprietor(s):
Enventure Global Technology
(Incorporated in USA - Delaware)
16200-A Park Row, Houston, Texas 77084,
United States of America

(74) Agent and/or Address for Service:
Haseltine Lake & Co
Redcliff Quay, 120 Redcliff Street,
BRISTOL, BS1 6HU, United Kingdom

BEST AVAILABLE COPY

184

GB 2 400 126 B - continuation

(58) INT CL^{7} **E21B**
Other: **EPODOC, JAPIO, WPI, TXTE**
(FULLTEXT)



10
14
12
16
LOCKING DEVICE
18
20
ACTUATOR
32
22
24
ADJUSTABLE
EXPANSION
MANDREL
30
26
28

Fig. 1



10
14
12
16
LOCKING DEVICE
18
20
ACTUATOR
32
22
24
ADJUSTABLE
EXPANSION
MANDREL
30
26
28

Fig. 2



10
14
12
16
LOCKING DEVICE
18
20
32
ACTUATOR
22
30
24
24a
ADJUSTABLE
EXPANSION
MANDREL
28
26

Fig. 3



10
14
12
16
LOCKING DEVICE
18
20
30
ACTUATOR
32
22
24
24a
ADJUSTABLE
EXPANSION
MANDREL
26
28

Fig. 4



10
14
16
LOCKING DEVICE
12
18
20
30
ACTUATOR
22
32
24
24a
ADJUSTABLE
EXPANSION MANDREL
26
28

Fig. 5



10
14
16
LOCKING DEVICE
12
18
20
30
ACTUATOR
22
24
24a
32
ADJUSTABLE
EXPANSION
MANDREL
26
28

Fig. 6



10
14
16
LOCKING DEVICE
12
18
20
ACTUATOR
30
22
32
34
36
24a
ADJUSTABLE
EXPANSION
MANDREL
24
26
38
28

Fig. 6a



100
14
12
16
LOCKING DEVICE
18
20
ACTUATOR
32
22
24
ADJUSTABLE
EXPANSION
MANDREL
30
26
28
40a
40b

Fig. 7



100
14
12
16
LOCKING DEVICE
18
20
ACTUATOR
32
22
24
ADJUSTABLE
EXPANSION
MANDREL
30
28
26
40a
40b

Fig. 8



100
14
12
16
LOCKING DEVICE
18
20
ACTUATOR
32
22
30
24
ADJUSTABLE
EXPANSION
MANDREL
40a
40b
26
28

Fig. 9



100
14
12
16
LOCKING DEVICE
18
20
32
ACTUATOR
22
30
24
24a
ADJUSTABLE
EXPANSION
MANDREL
40a
40b
26
28

Fig. 10



100
14
12
16
LOCKING DEVICE
18
20
30
ACTUATOR
32
22
24
24a
ADJUSTABLE
EXPANSION
MANDREL
26
28
40a
40b

Fig. 11



100
14
16
LOCKING DEVICE
12
18
20
ACTUATOR
30
22
32
24
24a
ADJUSTABLE
EXPANSION
MANDREL
26
28
40a
40b

Fig. 12



100
14
16
LOCKING DEVICE
12
18
20
ACTUATOR
30
22
24
24a
32
ADJUSTABLE
EXPANSION
MANDREL
26
28
40a
40b

Fig. 13



200
14
16
LOCKING DEVICE
18
20
12
32
ACTUATOR
22
202
30
UPPER ADJUSTABLE EXPANSION MANDREL
204
LOWER ADJUSTABLE EXPANSION MANDREL
206
26
28

Fig. 14



200
14
16
LOCKING DEVICE
18
20
12
32
ACTUATOR
30
22
202
UPPER ADJUSTABLE EXPANSION MANDREL
204
LOWER ADJUSTABLE EXPANSION MANDREL
206
26
28

Fig. 15



200
14
16
LOCKING DEVICE
18
20
12
ACTUATOR
32
22
30
202
UPPER ADJUSTABLE EXPANSION MANDREL
204
206a
206
LOWER ADJUSTABLE EXPANSION MANDREL
26
28

Fig. 16



200
14
16
LOCKING DEVICE
18
20
12
ACTUATOR
32
22
30
202
UPPER ADJUSTABLE EXPANSION MANDREL
204
206a
LOWER ADJUSTABLE EXPANSION MANDREL
206
12a
26
28

Fig. 17



200
14
16
LOCKING DEVICE
18
20
12
ACTUATOR
30
32
22
202
12a
UPPER
ADJUSTABLE
EXPANSION
MANDREL
204
206a
LOWER
ADJUSTABLE
EXPANSION
MANDREL
206
26
28

Fig. 18



200
14
16
LOCKING DEVICE
18
12
ACTUATOR
32
30
20
22
202a
202
12a
UPPER
ADJUSTABLE
EXPANSION
MANDREL
204
LOWER
ADJUSTABLE
EXPANSION
MANDREL
206
26
28

Fig. 19



200
14
16
LOCKING DEVICE
12
18
20
32
ACTUATOR
30
22
202a
202
UPPER
ADJUSTABLE
EXPANSION
MANDREL
204
12b
LOWER
ADJUSTABLE
EXPANSION
MANDREL
206
12a
26
28
206a

Fig. 20



200
14
16
LOCKING DEVICE
18
20
ACTUATOR
12
30
22
32
202
202a
UPPER
ADJUSTABLE
EXPANSION
MANDREL
204
12b
LOWER
ADJUSTABLE
EXPANSION
MANDREL
206
12a
26
28

Fig. 21



200
14
16
LOCKING DEVICE
18
20
12
ACTUATOR
22
202
202a
UPPER
ADJUSTABLE
EXPANSION
MANDREL
204
30
LOWER
ADJUSTABLE
EXPANSION
MANDREL
206
32
12b
26
28
12a

Fig. 22



300
306a
304
306b
302
306c
306d

Fig. 23



400
434b
432b
436b
434c
432a
434a
432c
436c
434d
436a
432d
436d
402
700
404
404b
414
414a
406l
424a
412
406f
438a
406i
428p
410
406k
412a
406d
406
406h
428b
428
428e
428f
408a
428g
402a
404a
406c
406b
406a
454a
428i
428d
428j
428k
13/132
408b
428a
428l
468
404c
422
418
412d
424b
412c
454
438b
406j
410a
416
420
412b
406e
426
406g
428c
432l
436l
434f
432h
436h
432i
436i
434h
434i
432g
436g
434g

Fig. 24a



400
436b
434b
432b
436a
434a
432a
428p
428
436d
434d
432d
428f
436c
434c
432c
428e
432e
434e
436e
428h
448a
428n
440b
454
440
440d
444a
442a
446a
442b
444b
446b
440f
442c
444c
446c
440g
442d
444d
446d
442e
444e
446e
452a
450b
440n
450d
468
450
428l
428d
428j
428g
428l
454a
428l
440e
440l
440h
440m
450a
428a
440a
440p
440c
448b
428o
428m
436j
434j
432j
440i
442f
444f
446f
442g
440k
446h
444h
442h
440j
446g
444g
442i
444i
446i
442j
444j
446j
450c
452b
440o
700
432f
434f
436f
432g
434g
436g
432h
434h
436h
428k
432i
434i
436i

Fig. 24b



400
458
458a
456
456a
700
450
450a
468
450d
454
452a
452b
450b
450c
454a
440n
440o

Fig. 24c



400
456
700
458
456a
458a
462a
460b
458b
460
476b
464a
466
466a
464b
476d
472
474a
475a
472b
484b
486a
480
482a
480a
478
484
484a
478a
478d
470
478b
478c
474c
474d
475b
474
464c
464
476a
476
458c
460c
462b
460a
464d
476c
472a
472c
474b
476e
486b
484c
482b
480b

Fig. 24d



400
522
700
522a
470
492a
492
492b
492c
494a
494b
486g
486d
486f
486e
486b
484e
488
490a
490b
484d
486
486a
486c
524
524a
484
484a

Fig. 24e



400
529
502a
700
502b
504a
496d
496b
500a
492d
496
526b
526
526d
492a
522
529a
496g
496l
498
522a
526a
502
470
502c
504b
496e
492e
500b
496c
496a
526c
528
492

Fig. 24f



400
528
502a
530d
530
530b
502d
506
508a
506b
506d
514a
512b
700
512a
534
528a
530a
510
506f
506g
534a
512
512c
514b
506e
502e
508b
506c
506a
530c
532
502
470

Fig. 24g



400
534
700
512a
534a
536f
536b
536d
548a
536
536a
538
540
540a
540c
542
546
544
544a
518
516f
516b
516
512d
520a
516e
536c
548b
536e
540b
540c
516d
512e
520b
516c
516a
512
470

Fig. 24h



400
544
544a
550
552c
552
552a
552b
554
554a
554b
554c
556a
556b
558
560
560a
562
562a
562b
564
566
566a
568
570
572
574
576
578
580
582
584
586
588
588a
700
470

Fig. 24i



400
700
610
610a
608a
622
610b
612
610c
624
622c
588g
588f
588e
588d
622b
618
618a
620
608
622a
614
608b
614a
616
588h
606
604
588a
602
602
600
588c
600
598
596
590c
594
590d
470a
588b
470b
592a
592b
590a
590b
588
590
470

Fig. 24j



400
700
654b
654a
654c
654
656
656
646a
650a
650
652
652
646
648a
644a
644
648
638a
638b
644b
644c
638
642a
644d
630
630a
640
642
628
636
634
632
626
628a
626a
610
610a

Fig. 24k




Fig. 25a




FIG. 25b




Fig. 25c




Fig. 25d




Fig. 25e




Fig. 25f




Fig. 25g



400
412
406e
424b
406d
424a
412i
412b
406a
412d
406i
420
406k
418
416
414
410
406

Fig. 25h



400
402
700
404
404a
402a
404b
404c
408a
408b
406c
406b
702
406a
454a
454
406
406a
406b
406c
406d
406e
406f
406g
406h
406i
406j
406k
406l
410
410a
412
412a
412b
412c
412d
414
414a
416
418
420
422
424a
424b
426
428
428a
428b
428c
428d
428e
428i
428j
428p
432a
432b
432f
432g
434a
434b
434f
434g
436a
436b
436f
436g
438a
438b
468

Fig. 26a



400
702
454a
450a
468
450
700
428
428g
428l
440e
440l
440h
440m
440n
440o
440a
440d
440
454
440b
440g
440k
428h
428n
428o
428m
448a
448b
432e
432d
432c
432i
432h
432j
434e
434d
434c
434h
434l
434j
436e
436d
436c
436h
436i
436j
442b
442d
442a
442e
442c
442h
442i
442g
444b
444d
444e
444h
444j
444i
444f
444g
446a
446b
446d
446e
446c
446h
446j
446i
446f
440f
440j
452a
450b
452b
450c
450d
440c
440i
442f

Fig. 26b




Fig. 26c



400
456
700
458
458a
456a
462a
460b
458b
460
476b
464a
466a
466
464b
476d
472
474a
472b
475a
484b
486a
480
482a
480a
478
484
484a
478d
478a
470
478b
480b
482b
484c
486b
476e
474b
472c
472a
476c
464d
460a
458c
460c
462b
476
476a
702
464
464c
474
475b
474d
474c
478c

Fig. 26d



400
522
522a
700
702
470
492
492a
492b
492c
494a
494b
486d
486b
486g
486f
486e
486c
490a
488
490b
484d
486a
484e
486
524
484a
524a
484

Fig. 26e



400
522
522a
492a
526d
526
526a
526b
526c
528
492
706
702
492d
496
500a
496b
498
504a
496d
502b
496f
496g
700
529
502a
529a
502
470
502c
504b
496e
496c
500b
492e
496a

Fig. 26f



400
534
534a
512a
512b
512
512c
514a
514b
506g
506f
506d
506b
506e
502e
508a
510
508b
502d
506
506c
506a
708
702
530b
530c
530
532
530d
530a
700
502
529a
502a
529
470

Fig. 26g



400
534
700
512a
534a
702
512
470
536
536a
538
536b
536f
536d
548a
540a
540c
710
546
542
540
540b
548b
536e
536c
512d
516b
516f
516
520a
516e
518
544
544a
516a
516c
520b
512e
516d

Fig. 26h



400
544
544a
550
552a
552c
554
554b
554a
556a
558
552
552b
556b
554c
560
560a
470
562
562a
562b
564
566
566b
566a
568
570
572
574
576
578
580
582
584
586
588
700
702

Fig. 26i



400
566
588
566a
588a
588b
590
590a
592a
470a
590c
598
588c
594
702
600
604
616
608b
608
622a
588h
614a
606
600
596
590d
590b
592b
470b
588d
618
620
614
618a
622b
588f
610c
622c
588e
588g
624
612
608a
610b
622
610a
610
700
470

Fig. 26j



400
610
610a
626
626a
628
628a
630
630a
632
634
636
638
638a
638b
640
642
642a
644
644a
644b
644c
644d
646
646a
648
648a
650
650a
652
654
654a
654b
654c
656
700
702
704

Fig. 26k




Fig. 27a




Fig. 27b



400
402
700
404
402a
404a
408a
404b
406c
414
410
414a
406k
406l
412a
406d
424a
412
406
406f
406h
438a
428b
428
406i
428p
432a
434a
436a
432b
434b
436b
428e
406b
702
406a
454a
428d
428j
702
428j
436g
434g
432g
428i
436f
434f
432f
428a
406j
428c
438b
406g
454
426
412c
406e
424b
412b
412d
420
418
416
422
410a
404c
408b
468

Fig. 28a



400
450
468
700
702
450a
450b
450d
452a
452b
450c
440n
440o
440m
440h
440l
440e
440g
440k
440j
440d
440b
440
454
454a
440a
440c
440i
428n
428h
428l
428o
428m
428g
428
448a
448b
446a
446b
446c
446d
446e
446h
446j
446i
446g
446f
444a
444b
444c
444d
444e
444h
444j
444i
444g
444f
442a
442b
442c
442d
442e
442h
442j
442i
442g
442f
436e
436d
436c
436h
436j
436i
434e
434d
434c
434h
434j
434i
432e
432d
432c
432h
432j
432l
428f
428k

Fig. 28b



400
456
700
458
462a
460b
458b
476b
464a
466a
464b
476d
472
474a
472b
475a
484b
486a
480
482a
480a
478
484
456a
458a
476a
476
702
458c
460c
462b
460a
464d
476c
464
464c
466
474
475b
474d
472a
472c
474b
476e
486b
484c
482b
480b
478b
478c
474c
478a
484a
702
478d
470
468

Fig. 28c



400
522
522a
700
702
470
492
492a
492b
492c
494a
494b
486d
486b
486g
486f
486e
486c
490a
488
490b
484d
486
486a
484e
524
524a
484
484a

Fig. 28d



400
522
492
526d
526
526b
700
706
496
492d
500a
496b
496d
504a
496f
529
502a
529a
502
502c
504b
496e
492e
500b
496c
496a
498
502b
496g
702
522a
526a
528
492a
470

Fig. 28e



400
529
502
530d
530
530b
700
708
506
502d
508a
506b
506d
514a
512b
512a
534
529a
530a
702
510
506f
506g
534a
512
512c
514b
506e
502e
508b
506c
506a
532
530c
502a
470

Fig. 28f



400
534
512a
534a
702
536
536f
536b
548a
536d
540a
540c
546
542
540
540b
548b
536e
536c
536a
538
512
470
516a
516c
520b
512e
516d
516e
512d
520a
516b
516
516f
544
544a
518
710
700

Fig. 28g



400
544
544a
552c
558
550
552
552a
552b
556a
554
554b
554c
556b
554a
560
560a
562
562a
562b
564
566
566a
566b
568
570
572
574
576
578
580
582
584
586
588
700
702
470

Fig. 28h



400
610
610a
700
608a
622
610b
612
610c
624
622c
588g
588f
588e
588d
622b
618
618a
620
608
614
622a
608b
588h
616
614a
606
604
600
702
600
598
596
594
590d
590c
588c
592a
592b
590a
590b
588b
588
588a
590
566a
566
470

Fig. 28i



400
470
610
610a
626
626a
628
628a
630
630a
632
634
636
638
638a
638b
640
642
642a
644
644a
644b
644c
644d
646
646a
648
648a
650
650a
652
654
654a
654b
654c
656
700
702
704

Fig. 28j



400
402
700
404
404a
402a
408a
404b
414
410
414a
406k
406l
412a
424a
426d
412
406
406f
406h
438a
428b
428
406i
428p
434a
432a
436a
432b
436b
434b
428e
428j
436g
434g
432g
428i
436f
434f
432f
428a
406j
428c
438b
454
406g
426
412c
406e
424b
412b
412d
420
418
416
422
410a
404c
408b
406c
406b
406a
454a
428d
428j
702
468

Fig. 29a



400
450
468
702
700
450a
450d
452b
450c
446j
444j
442j
446i
444i
442i
440o
440m
440h
440k
446h
444h
442h
440j
446g
444g
442g
440l
440e
428l
440i
442f
444f
446f
440a
440c
428o
448b
428m
436j
434j
432j
428g
436d
434d
432d
428f
436c
434c
432c
428
432h
434h
436h
428k
432i
434i
436i
454a
454
440
440b
428n
448a
428h
436e
434e
432e
446a
444a
442a
440d
442d
444d
446d
442e
444e
446e
452a
450b
440n
442b
444b
446b
440f
442c
444c
446c
440g

Fig. 29b




Fig. 29c



400
456
456a
700
702
458
458a
462a
458b
460b
460
476b
464a
466a
466
464b
476d
472
474a
472b
475a
484b
486a
480
482a
480a
478
484
702
484a
478d
478a
470
478b
480b
482b
478c
474c
484c
486b
476e
474b
472c
472a
474
475b
474d
476c
464d
460a
458c
460c
462b
476
476a
464
464c
468

Fig. 29d



400
522
492a
492b
494a
486d
486b
490a
484d
486
700
524
484a
524a
484
522a
702
488
486a
484e
490b
486c
494b
486e
492c
486g
486f
470
492

Fig. 29e



400
492d
500a
496b
496d
504a
496f
529
529a
502a
502
502c
504b
496e
492e
500b
496c
496a
496
498
502b
496g
706
700
702
470
526b
526c
526
526a
526d
528
522a
492
492a
522

Fig. 29f



400
529
502
530d
530
530b
700
708
506
502d
508a
506b
506d
514a
512b
512a
534
529a
702
530a
702
510
506f
506g
534a
512
512c
514b
506e
502e
508b
506c
506a
532
530c
502a
470

Fig. 29g



400
700
534
534a
512a
702
536b
536f
536
536d
548a
540a
540c
542
546
710
512d
516e
516b
516f
516
520a
518
544a
544
516a
516c
520b
512e
516d
540
540b
548b
536e
536c
536a
538
512
470

Fig. 29h



400
544
544a
550
552
552a
552b
552c
554
554a
554b
554c
556a
556b
558
560
560a
562
562a
562b
564
566
566a
566b
470
702

Fig. 29i



400
564
566
570
572
580
582
566
588
592a
590a
590c
566a
702
702
588a
588b
588c
594
590
700
586
584
578
576
574
568
470
590b
590d
592b

Fig. 29j



400
700
598
588
600
602
604
608b
588d
618a
588f
622b
622
610c
608
588b
588c
594
588a
702
616
588e
622a
622c
590
470
596
600
602
606
614a
614
620
618
588g
624
608a
612

Fig. 29k



400
470
700
610c
610
626a
626
636
640
630
642a
644d
644b
638a
648
646
622c
702
610b
610a
608a
612
628a
632
634
628
642
630a
638
644c
638b
644
648a
644a

Fig. 29l



400
700
654
654b
654a
654c
656
650a
646a
470
650
652
652
648a
704
646
644
648
638a
644a
638b
644c
644b
638

Fig. 29m



PULL TO RETRACT
PUSH TO EXPAND
610
610b
608a
612
624
622c
588f
588e
588g
622
588d
618
618a
620
622a
622b
400
608
588
588a
614
608b
588h
614a
616
606
604
600
702
596

Fig. 30a



PULL TO RETRACT
PUSH TO EXPAND
400
610
610b
612
608a
624
622c
588f
588e
588g
622
588d
618
618a
620
622a
622b
608
588
588a
614
608b
588h
614a
616
606
604
600
600
702
596

Fig. 30b



400
600
602
604
616
608b
608
588d
618a
588f
624
622
610
PULL TO RETRACT
702
588h
588a
622a
588e
622c
65/132
596
600
602
606
614a
614
588
622b
620
618
588g
608a
612
610b
PUSH TO EXPAND

Fig. 30c



400
402
700
404
404a
402a
408a
406c
404b
414
410
414a
406k
406l
412a
406d
424a
412
406
406i
406h
406f
438a
428b
428
406i
428p
432a
434a
436a
432b
434b
436b
428e
406b
702
406a
454a
428d
428j
702
428j
436g
434g
428i
436i
432g
434f
432f
428a
406j
438b
428c
406g
454
426
412c
406e
424b
412b
412d
420
418
416
422
410a
404c
408b
468

Fig. 31a



400
702
428g
428l
454a
428l
440e
440l
440h
440m
450a
702
468
450
440n
452a
450b
446e
444e
442e
446d
444d
442d
446c
442c
444c
440g
446b
444b
442b
440f
446a
444a
442a
436d
434d
432d
428f
436c
434c
432c
432e
434e
436e
428h
448a
428n
440b
454
440
440d
428
432h
434h
436h
428k
432i
434i
436i
432j
434j
436j
428m
448b
428o
440c
440a
440i
442f
444f
446f
442g
444g
446g
440j
442h
444h
440k
446h
442i
444i
446i
442j
444j
446j
450c
452b
440o
450d
700

Fig. 31b




Fig. 31c



400
456
456a
700
702
458
458a
462a
476
458b
460b
460
476c
464a
464
476a
476b
466a
466
464b
464c
472
476d
474a
475b
472b
475a
474d
484b
486a
474c
480
478c
478b
480a
482a
478d
484
478a
470
478
480b
482b
484c
486b
476e
474b
472c
474
472a
464d
460a
458c
460c
462b
468

Fig. 31d



400
700
478
480
482a
480a
478d
524
484
484a
522
522a
702
524a
478a
480b
482b
470

Fig. 31e



400
522
484
484a
470
522a
702
700
486
484d
490a
486b
486d
494f
492b
526d
526
526b
492
706
529
492a
702
529a
526a
526c
528
492c
494b
486e
490b
484e
486c
488
486a
486f
486g

Fig. 31f



400
492
492a
492d
492e
496
496a
496b
496c
496d
496e
496f
496g
498
500a
500b
502
502a
502b
502c
504a
504b
529
529a
530
530a
530b
530c
530d
532
534
534a
700
702
706
708

Fig. 31g



400
534
502
534a
700
708
470
502d
506
508a
506b
506d
514a
512b
536f
536b
548a
536d
540a
512a
544
540c
544a
542
546
540
536e
548b
540b
536c
538
512c
514b
506e
502a
508b
506c
506a
506f
506g
536
536a
510
702
710
512

Fig. 31h



400
544
512
512a
710
470
700
544a
702
512d
516e
516b
520a
516f
516
552c
552a
550
556a
554b
554
554a
560
554c
556b
552b
552
516a
516c
520b
512e
516d
516
518
558

Fig. 31i



400
554
554a
560
560a
562
562a
562b
564
566
566a
566b
568
570
572
574
576
578
580
582
584
586
588
588a
590
700
702
470

Fig. 31j



400
566
566a
588
470
590a
598
588
600
602
604
608b
588d
618a
618
608
622
622c
610
620
614
614a
606
602
600
596
590d
590b
588b
590
700
702
588c
594
588a
616
588e
622a

Fig. 31k



400
588
588a
588d
588e
588f
588g
610
610a
610b
610c
612
614
618
618a
620
622
622a
622c
624
626
626a
628a
632
634
638
700
702
470
608
608a

Fig. 311



400
650
652
704
646
648
638a
644b
640
636
470
630
638
626a
626
642a
644d
702
644a
644
642
630a
638
644c
638b
648a
652
700

Fig. 31m



400
700
654
654b
654a
654c
656
656
650a
646a
650
704
470
646
648

Fig. 31n



400
402
700
404
404a
402a
408a
404b
414
410
414a
406k
406l
412a
424a
426d
412
406
406f
406h
438a
406i
428
428p
432a
434a
436a
432b
434b
436b
428e
712
428j
428d
454a
406a
406b
406c
408b
404c
410a
422
416
418
420
412d
412b
424b
406e
412c
426
454
438b
406g
428a
406j
432l
434l
436l
428i
432g
434g
436g
468

Fig. 32a



400
712
712
428
428g
428l
454a
440a
440e
440l
440h
440m
450a
468
450
700
81/132

Fig. 32b




Fig. 32c



400
522
522a
484a
484
470
712
524
524a
478a
478d
480a
480b
482a
482b
480
478b
478c
484c
486a
484b
486b
474c
474d
475a
472b
478
474a
475b
474b
472
472c
476d
476e
474
464b
472a
464
464c
464d
476c
476a
464a
460a
460
458a
476b
460b
458c
460c
462a
462b
466
466a
458a
458
476
468
700

FIG. 32d



400
484
484a
470
486
484d
490a
486d
486b
494a
526d
526
526b
492b
492
706
529
492a
712
522a
522
700
484e
490b
486c
494b
486e
492c
528
526c
526a
529a
488
486a
486f
486g

Fig. 32e



400
492a
492d
492e
492
470
496
496a
496b
496c
496d
496e
496f
496g
498
500a
500b
502
502a
502b
502c
504a
504b
529a
530
530a
530b
530c
530d
532
534
534a
700
706
708
712
712

Fig. 32f



400
534
502
700
470
708
712
534a
502d
506
508a
506b
506d
514a
512b
536f
536b
548a
536d
540a
512a
544
506a
510
506f
506g
536
536a
546
542
540c
544a
540
536e
548b
540b
536c
538
512c
514b
506e
502e
508b
506c
710
512

Fig. 32g



400
544
512
512a
710
712
470
700
544a
516
516e
512d
516b
516f
552c
550
552a
556a
554b
554
554a
560
554c
556b
552b
552
516a
516c
520b
512e
516d
520a
518
558

Fig. 32h



400
554a
562
564
566
570
572
580
582
566
588
590
598
600
604
616
608b
608
614
614a
606
596
590d
700
586
584
578
576
574
568
470
560
554
560a
566a
562a
562b
712
588b
588c
594
588a
588h

Fig. 32i



400
600
604
588
608b
608
618a
622b
610c
610
632
634
630
636
640
626
642a
644b
644d
646
704
470
644
644a
712
638a
638b
644c
638
630a
642
628
626a
610a
622
610b
608a
612
624
622c
588f
588d
588g
588e
618
620
622a
614
614a
606
616
588a

Fig. 32j



400
700
654
654b
654a
654c
656
656
650a
646a
650
704
648a
646
644
648
644a
638a
638b
644c
644b
638
470
712

Fig. 32k



400
434b
402
700
404
404b
414
410
414a
406k
406l
412a
424a
426d
412
406
406f
406h
438a
428b
406i
428
428p
432a
434a
436a
432b
436b
408a
428e
402a
404a
406c
406b
714
406a
454a
428d
428j
714
408b
428j
468
404c
410a
422
416
418
420
412d
412b
424b
406e
412c
426
454
406g
438b
428c
406j
428a
432f
434f
436f
428i
432g
434g
436g

Fig. 33a



400
714
428g
428l
454a
428l
440e
440l
440h
440m
450a
714
428
432h
434h
436h
428k
432i
434i
436i
432j
434j
436j
428m
448b
428o
440c
440a
440i
442f
444f
446l
442g
444g
446g
440j
442h
444h
446h
440k
442i
444i
446i
442j
444j
446j
450c
452b
440o
450d
700
468
450
440n
452a
450b
446e
444e
442e
446d
444d
442d
442b
444b
446b
440f
446c
442c
444c
440g
446a
444a
442a
440b
454
440
440d
436d
434d
432d
428f
436c
434c
432c
432e
434e
436e
428h
448a
428n

Fig. 33b




Fig. 33c



400
700
458
458a
456a
462a
460b
458a
460
476c
464a
464
464b
476d
472
474a
472b
475a
484b
486a
480
482a
480a
484
484a
484a
478d
478b
478c
474c
474d
475b
476a
476b
464c
464d
460a
460c
458c
462b
476
468
472a
474
476e
472c
474b
478
486b
484c
482b
480b
478a

Fig. 33d



400
522
522a
484
470
714
700
524
524a
484
466
484a
484a
468
478d
478a
478
480a
480b
482a
480
482b
484c
484b
474c
486b
486a
474d
474

Fig. 33e



400
700
484
484a
522
522a
524
524a
714
470
486
486a
486b
486c
486d
486e
488
490a
490b
484d
484a

Fig. 33f



400
484a
484d
484
486
490a
486b
486d
494a
492b
700
522a
486g
486l
714
522
526d
526
526b
706
492a
488
486a
484e
490b
486c
486e
494b
492c
492
470
528
526a
526c
529a
529

Fig. 33g



400
529
492a
706
714
529a
496
492d
500a
496b
496d
504a
502b
502a
502
534
714
496g
502c
504b
496e
496c
500b
492e
700
492
470
496a
498
496f

Fig. 33h



400
529
529a
530d
530b
530a
700
502
714
502a
534
534a
708
506
502d
508a
506b
506d
514a
512b
512a
506g
506f
510
506c
506a
508b
502e
506e
514b
512c
512
532
530c
530
470

Fig. 33i



400
512a
534
534a
512
536b
536f
536
536a
538
536c
548a
536d
540a
540c
546
542
540
540b
536e
548b
710
544
544a
714
700
470
516
516b
520a
512d
516e
516f
516a
516c
520b
512e
516d
518

Fig. 33j



566a
566
562b
564
562a
562
566b
560a
560
554a
554
554b
554c
556a
556b
552a
552b
550
558
552
400
552c
544a
544
470
700
714

Fig. 33k



400
554
700
562
564
566
570
572
580
582
588
590
588a
588b
586
584
578
576
574
568
470
554
560
554a
566b
562a
562b
566a
714

Fig. 331



400
566
566a
588
700
588b
590d
598
600
604
608b
616
608
618a
622b
588e
622c
618
620
588d
622
622a
614a
588h
606
714
594
588c
596
470
588a
590

Fig. 33m



400
630
630a
626
628
626a
634
700
632
470
610
610a
624
714
588g
588f
588e
622c
608

Fig. 33n



400
704
646
644
648
638a
644a
638b
644b
644c
638
640
636
700
642
714
626
470
630
630a
628
626a

Fig. 33o




Fig. 33p



400
402
404
404a
402a
700
716
408a
408b
404b
404c
406c
406b
410
410a
414
414a
406k
406l
406a
714
416
418
420
422
406d
412a
412d
424a
424b
406e
412b
406f
412
406
406h
406g
454
412c
438a
426
428b
438b
406i
428c
428
454a
406j
428p
428a
428d
434a
428j
434f
436a
432f
432a
436f
436b
428i
434g
434b
436g
432b
714
432g
428e
428l

Fig. 34a



400
714
716
450
450a
454
454a
700
428
428g
428h
428i
428k
428m
428n
428o
432c
432d
432e
432h
432i
432j
434c
434d
434e
434h
434i
434j
436c
436d
436e
436h
436i
436j
440a
440b
440c
440d
440e
440f
440g
440h
440i
440j
440k
440l
440m
440n
440o
442a
442b
442c
442d
442e
442f
442g
442h
442i
442j
444a
444b
444c
444d
444e
444f
444g
444h
444i
444j
446a
446b
446c
446d
446e
446f
446g
446h
446i
446j
448a
448b
450b
450c
450d
452a
452b

Fig. 34b




Fig. 34c



400
462a
460b
458b
476c
460
464a
464
464b
476d
472
474a
472b
475a
484b
486a
480
482a
480a
484
484a
478d
478a
484a
478b
478c
482b
480b
484c
486b
474c
474d
475b
478
474b
472c
476e
474
472a
464d
460a
458c
460c
462b
476
476b
476a
464c
458a
458
716
700
714
468

Fig. 34d



400
522
492
492a
492b
492c
714
494f
494b
486g
486f
486d
486b
486c
486e
490a
490b
488
484d
484a
486a
486
470
522a
466
700
468
524
716
524a
484
484a

Fig. 34e



400
522
492
526d
526
526b
700
714
706
492a
492d
496
500a
496b
496d
504a
496f
529
502a
529a
502b
498
496g
502
502c
504b
496e
492e
500b
496c
496a
470
528
526c
716
522a
526a

Fig. 34f



400
529
529a
502
530d
530
530a
530b
700
502a
708
506
502d
508a
506b
506d
514a
512b
512a
534
534a
506g
506f
510
502e
506c
508b
506e
514b
512c
512
506a
470
530c
532
716
714

Fig. 34g



400
544
516f
516
516b
516a
520a
516c
512d
520b
516e
512e
516d
544a
710
542
546
540c
540
540a
540b
548a
540
536d
548b
536b
536e
536a
536c
536
538
536f
512a
714
470
534
534a
512
700
716

Fig. 34h



400
700
544
544a
714
716
470
550
552
552a
552b
552c
554
554a
554b
554c
556a
556b
558
560
560a
562
562a
562b
564
566
566a
566b
568
574

Fig. 34i



400
604
600
598
590d
588b
588
566
582
580
716
572
570
606
600
596
700
590
470
586
584
578
576
574
568
588a
594
588c
714
566a

Fig. 34j



400
626
626a
632
470
610a
610
608a
622
610b
612
610c
622c
624
588g
588l
588d
588e
618
620
618a
622
608
622a
614
616
608b
614a
606
604
600
714
600
700
588a
716
588

Fig. 34k



400
700
610
588l
608
588
634
632
630
626
626a
714
610a
610b
622c
630a
628
470
608a
612
624
588g

Fig. 341



400
402
700
404
404a
404b
408a
406c
406b
406k
414
410
414a
406l
412a
424a
406d
412
406
406a
406i
406h
454a
426
412c
406e
424b
412b
412d
420
418
416
422
410a
404c
408b
406
468
402a
714

Fig. 35a



400
406
700
714
468
454
454a
438a
438b
406i
406j
428
428a
428b
428c
428d
428e
428g
428i
428j
428l
428n
428o
428p
428m
428k
432a
432b
432c
432d
432e
432f
432g
432h
432i
432j
432l
434a
434b
434c
434d
434e
434f
434g
434h
434i
434j
436a
436b
436c
436d
436e
436f
436g
436h
436i
436j
440
440b
440c
440d
440e
440i
440j
440p
442b
442f
442g
444a
444b
444f
444g
446a
446b
446f
446g
448a
448b
454
454a

Fig. 35b



400
700
456
456a
468
450
714
450a
454
452a
452b
450b
450c
440m
440n
440o
446e
444e
442e
446j
444j
442j
440h
446d
444d
442d
440g
446c
444c
442c
440l
454a
440k
442h
444h
446h
442l
444i
446i

Fig. 35c



400
456
456a
700
714
458
458a
462a
458b
460b
476b
460a
464a
466a
466
464b
476d
472
474a
475a
472b
484b
486a
480
482a
480a
478
484
458c
460c
462b
476
476a
464
464c
474
475b
474d
474c
478c
478d
484a
470
468
460a
464d
476c
472a
472c
474b
476e
486b
484c
482b
480b

Fig. 35d



400
700
470
524
524a
484
522
522a
714
484d
486
486a
488
490a
490b
484e
486b
486d
494a
492a
492b
486f
486g
492
492c
494b
486e
486c

Fig. 35e



400
529
526b
526d
522
492a
492b
494a
486d
486b
490a
484d
486
700
526
526c
528
526a
714
470
492
522a
492c
494b
486e
486c
490b
484e
486a
488
486f
486g
484

Fig. 35f



400
526
492a
706
496
492d
500a
496b
496d
504a
502b
502
502a
700
502c
504b
496e
496c
500b
492e
496a
498
496f
496g
529a
714
529
492
470

Fig. 35g



400
502d
508a
506d
506b
512a
512b
514a
506g
506f
512
512c
514b
506e
502e
508b
506c
506a
506
510
708
534a
534
502a
714
502
700
530
530b
530c
530d
530a
532
529a
529
470

Fig. 35h



400
512a
534
534a
512
536f
536b
536d
548a
540a
540c
536
536a
538
546
542
536c
536e
548b
540b
540
544a
544
710
700
714
470
516f
516
516b
516a
520a
516c
518
520b
512d
512e
516e
516d

Fig. 35i



400
700
588
586
582
580
714
584
578
576
572
570
574
566a
568
566
562b
564
562a
562
566b
560a
560
554a
470
554
554b
554c
556a
556b
552a
552b
552
550
558
544a
544
552c

Fig. 35j



129/132
400
610
610a
622
610b
608a
700
624
622c
612
588g
588f
588d
588e
618a
618
620
622a
608
614
608b
718
616
614a
604
606
600
714
600
598
594
596
588c
590d
588a
588b
590
588
566a
470
566

Fig. 35k




Fig. 351



400
610a
610
610b
608a
612
624
622c
588f
588e
588g
720
622
588d
618
618a
620
622a
622b
608
588
614
588a
608b
588h
614a
616
606
604
600
702
600
596

Fig. 36a



400
610
610a
610b
608a
612
622c
624
588f
588e
588g
720
622
588d
618
618a
620
622a
622b
718
608
588
588a
614
608b
588h
614a
616
604
606
600
714
596

Fig. 36b

MONO DIAMETER WELLBORE CASING

This invention relates generally to forming and repairing wellbore casings to facilitate oil and gas exploration, and in particular to a method of radially expanding and plastically deforming a tubular member.

Conventionally, when a wellbore is created, a number of casings are installed in the borehole to prevent collapse of the borehole wall and to prevent undesired outflow of drilling fluid into the formation or inflow of fluid from the formation into the borehole. The borehole is drilled in intervals whereby a casing which is to be installed in a lower borehole interval is lowered through a previously installed casing of an upper borehole interval. As a consequence of this procedure the casing of the lower interval is of smaller diameter than the casing of the upper interval. Thus, the casings are in a nested arrangement with casing diameters decreasing in downward direction. Cement annuli are provided between the outer surfaces of the casings and the borehole wall to seal the casings from the borehole wall. As a consequence of this nested arrangement a relatively large borehole diameter is required at the upper part of the wellbore. Such a large borehole diameter involves increased costs due to heavy casing handling equipment, large drill bits and increased volumes of drilling fluid and drill cuttings. Moreover, increased drilling rig time is involved due to required cement pumping, cement hardening, required equipment changes due to large variations in hole diameters drilled in the course of the well, and the large volume of cuttings drilled and removed.

The present invention is directed to overcoming one or more of the limitations of the existing procedures for forming and/or repairing wellbore casings.

Summary of the Invention

According to the present invention there is provided a method of radially expanding and plastically deforming a tubular member, comprising:

positioning the tubular member within a preexisting structure;

radially expanding and plastically deforming a lower portion of the tubular member to form a bell section; and

radially expanding and plastically deforming a portion of the tubular member above the bell section,

wherein radially expanding and plastically deforming a lower portion of the tubular member to form a bell section comprises:

lowering an expansion device out of an end of the tubular member; and

pulling the expansion device through the end of the tubular member.

Preferably, positioning the tubular member within a preexisting structure comprises:

locking the tubular member to an expansion device.

Preferably, positioning the tubular member within a preexisting structure comprises:

unlocking the tubular member from an expansion device if the operating pressure within the preexisting structure exceeds a predetermined amount.

Preferably, positioning the tubular member within a preexisting structure comprises:

unlocking the tubular member from an expansion device if the position of an actuator coupled to the tubular member exceeds a predetermined amount.

Preferably, lowering an expansion device out of an end of the tubular member comprises:

lowering the expansion device out of the end of the tubular member; and

adjusting the size of the expansion device.

Preferably, the expansion device is adjustable to a plurality of sizes.

Preferably, the expansion device comprises a plurality of adjustable expansion devices.

Preferably, at least one of the adjustable expansion devices is adjustable to a plurality of sizes.

Preferably, pulling the expansion device through the end of the tubular member comprises:

gripping the tubular member; and

pulling an expansion device through an end of the tubular member.

Preferably, pulling the expansion device through the end of the tubular member comprises:

pulling the expansion device through the end of the tubular member using an actuator.

Preferably, radially expanding and plastically deforming a portion of the tubular member above the bell section comprises:

lowering an expansion device out of an end of the tubular member; and

pulling the expansion device through the end of the tubular member.

Preferably, lowering an expansion device out of an end of the tubular member comprises:

lowering the expansion device out of the end of the tubular member; and

adjusting the size of the expansion device.

Preferably, the expansion device is adjustable to a plurality of sizes.

Preferably, the expansion device comprises a plurality of adjustable expansion devices.

Preferably, at least one of the adjustable expansion devices is adjustable to a plurality of sizes.

Preferably, pulling the expansion device through the end of the tubular member comprises:

pulling the expansion device through the end of the tubular member using fluid pressure.

Preferably, pulling the expansion device through the end of the tubular member using fluid pressure comprises:

pressurizing an annulus within the tubular member above the expansion device.

Preferably, radially expanding and plastically deforming a portion of the tubular member above the bell section comprises:

fluidicly sealing an end of the tubular member; and

pulling the expansion device through the tubular member.

Preferably, the expansion device is adjustable.

Preferably, pulling the expansion device through the end of the tubular member comprises:

gripping the tubular member; and

pulling an expansion device through an end of the tubular member.

Preferably, radially expanding and plastically deforming a portion of the tubular member above the bell section comprises:

overlapping the portion of the tubular member above the bell section with an end of a preexisting tubular member; and

pulling an expansion device through the overlapping portions of the tubular member and the preexisting tubular member.

Preferably, pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member comprises:

gripping the tubular member; and

pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member.

Preferably, pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member comprises:

pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member using an actuator.

Preferably, pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member comprises:

pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member using fluid pressure.

Preferably, pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member using fluid pressure comprises:

pressurizing an annulus within the tubular member above the expansion device.

Preferably, the method further comprises:

injecting a hardenable fluidic sealing material into an annulus between the expandable tubular member and the preexisting structure.

Brief Description of the Drawings

Fig. 1 is a fragmentary cross-sectional illustration of the placement of an embodiment of an apparatus for radially expanding and plastically deforming a tubular member within a preexisting structure.

Fig. 2 is a fragmentary cross-sectional illustration of apparatus of Fig. 1 after displacing the adjustable expansion mandrel and the float shoe downwardly out of the end of the expandable tubular member.

Fig. 3 is a fragmentary cross-sectional illustration of the apparatus of Fig. 2 after expanding the adjustable expansion mandrel.

Fig. 4 is a fragmentary cross-sectional illustration of the apparatus of Fig. 3 after displacing the adjustable expansion mandrel upwardly to radially expand and plastically deform the expandable tubular member.

Fig. 5 is a fragmentary cross-sectional illustration of the apparatus of Fig. 4 after displacing the actuator, locking device, and tubular support member upwardly relative to the adjustable expansion mandrel and the expandable tubular member.

Fig. 6 is a fragmentary cross-sectional illustration of the apparatus of Fig. 5 after displacing the adjustable expansion mandrel upwardly to radially expand and plastically deform the expandable tubular member.

Fig. 6a is a fragmentary cross-sectional illustration of the apparatus of Fig. 6 that include one or more cup seals positioned above the adjustable expansion mandrel for defining an annular pressure chamber above the adjustable expansion mandrel.

Fig. 7 is a fragmentary cross-sectional illustration of the placement of an embodiment of an apparatus for drilling a borehole and radially expanding and plastically deforming a tubular member within the drilled borehole.

Fig. 8 is a fragmentary cross-sectional illustration of the apparatus of Fig. 7 after pivoting the drilling elements of the drilling member radially inwardly.

Fig. 9 is a fragmentary cross-sectional illustration of apparatus of Fig. 8 after displacing the adjustable expansion mandrel and drilling member downwardly out of the end of the expandable tubular member.

Fig. 10 is a fragmentary cross-sectional illustration of the apparatus of Fig. 9 after expanding the adjustable expansion mandrel.

Fig. 11 is a fragmentary cross-sectional illustration of the apparatus of Fig. 10 after displacing the adjustable expansion mandrel upwardly to radially expand and plastically deform the expandable tubular member.

Fig. 12 is a fragmentary cross-sectional illustration of the apparatus of Fig. 11 after displacing the actuator, locking device, and tubular support member upwardly relative to the adjustable expansion mandrel and the expandable tubular member.

Fig. 13 is a fragmentary cross-sectional illustration of the apparatus of Fig. 12 after displacing the adjustable expansion mandrel upwardly to radially expand and plastically deform the expandable tubular member.

Fig. 14 is a fragmentary cross-sectional illustration of the placement of an embodiment of an apparatus for radially expanding and plastically deforming a tubular member within a preexisting structure.

Fig. 15 is a fragmentary cross-sectional illustration of the apparatus of Fig. 14 after displacing the lower adjustable expansion mandrel and float shoe downwardly out of the end of the expandable tubular member.

Fig. 16 is a fragmentary cross-sectional illustration of the apparatus of Fig. 15 after expanding the lower adjustable expansion mandrel.

Fig. 17 is a fragmentary cross-sectional illustration of the apparatus of Fig. 16 after displacing the lower adjustable expansion mandrel upwardly to radially expand and plastically deform the expandable tubular member.

Fig. 18 is a fragmentary cross-sectional illustration of the apparatus of Fig. 17 after displacing the upper and lower adjustable expansion mandrels downwardly relative to the expandable tubular member.

Fig. 19 is a fragmentary cross-sectional illustration of the apparatus of Fig. 18 after collapsing the lower adjustable expansion mandrel and expanding the upper adjustable expansion mandrel.

Fig. 20 is a fragmentary cross-sectional illustration of the apparatus of Fig. 19 after displacing the upper adjustable expansion mandrel upwardly to radially expand and plastically deform the expandable tubular member.

Fig. 21 is a fragmentary cross-sectional illustration of the apparatus of Fig. 20 after displacing the tubular support member, the locking device, and the actuator upwardly relative to the upper adjustable expansion mandrel and the expandable tubular member.

Fig. 22 is a fragmentary cross-sectional illustration of the apparatus of Fig. 21 after displacing the upper adjustable expansion mandrel upwardly to radially expand and plastically deform the expandable tubular member.

Fig. 23 is a fragmentary cross-sectional illustration of a mono diameter wellbore casing formed using one or more of the apparatus of Figs. 1-22.

Figs. 24a-24k are fragmentary cross sectional illustrations of the placement of an exemplary embodiment of an apparatus for radially expanding and plastically deforming a tubular member within a wellbore that traverses a subterranean formation.

Fig. 25a-25f are fragmentary cross sectional and perspective illustrations of the expansion cone assembly of the apparatus of Figs. 24a-24k.

Fig. 25g is a perspective illustration of a float shoe locking dog.

Fig. 25h is a fragmentary cross sectional illustration of the design and operation of the casing gripper locking dogs.

Figs. 26a-26k are fragmentary cross sectional illustrations of the apparatus of Figs. 24a-24k after expanding the expansion cone assembly.

Figs. 27a-27b are a fragmentary cross sectional and perspective illustrations of the expansion cone assembly of the apparatus of Figs. 26a-26k.

Figs. 28a-28j are fragmentary cross sectional illustrations of the apparatus of Figs. 26a-26k during the upward displacement of the expansion cone assembly by the actuators to radially expand and plastically deform a portion of the casing.

Figs. 29a-29m are fragmentary cross sectional illustrations of the apparatus of Figs. 28a-28j after the collapse of the expansion cone assembly.

Fig. 30a-30c are fragmentary cross sectional illustrations of the process for collapsing the expansion cone assembly of the apparatus of Figs. 29a-29m.

Figs. 31a-31n are fragmentary cross sectional illustrations of the apparatus of Figs. 29a-29m after the plastic deformation and radial expansion of the sealing sleeve and the disengagement of the casing from the locking dogs of the casing lock assembly.

Figs. 32a-32k are fragmentary cross sectional illustrations of the apparatus of Figs. 31a-31n after setting down the apparatus onto the bottom of the wellbore to open the bypass valve in the shoe and expand the expansion cone assembly.

Figs. 33a-33p are fragmentary cross sectional illustrations of the apparatus of Figs. 32a-32k during the radial expansion and plastic deformation of the casing.

Figs. 34a-34l are fragmentary cross sectional illustrations of the apparatus of Figs. 33a-33p during the radial expansion and plastic deformation of a portion of the casing that overlaps within a preexisting wellbore casing within the wellbore.

Figs. 35a-35l are fragmentary cross sectional illustrations of the apparatus of Figs. 28a-28j during the emergency collapse of the expansion cone assembly.

Figs. 36a-36b are fragmentary cross sectional illustrations of several exemplary embodiments of the operation of the pressure balance piston.

Detailed Description of the Illustrative Embodiments

Referring to Fig. 1, an exemplary embodiment of an apparatus 10 for radially expanding and plastically deforming a tubular member 12 includes a tubular support member 14 that extends into the tubular member that is coupled to an end of a locking device 16 for controllably engaging the tubular member. Another end of the locking device 16 is coupled to a tubular support member 18 that is coupled to an end of an actuator 20. Another end of the actuator 20 is coupled to a tubular support member 22 that is coupled to an end of an adjustable expansion mandrel 24 for radially expanding and plastically deforming the tubular member 12. Another end of the adjustable expansion mandrel 24 is coupled to a tubular support member 26 that is coupled to an end of a float shoe 28 that mates with and is at least partially received within a lower end of the tubular member 12. In an exemplary embodiment, the locking device 16, the tubular support member 18, the actuator 20, the tubular support member 22, the adjustable expansion mandrel 24, and the tubular support member 26 are positioned within the tubular member 12.

In an exemplary embodiment, the tubular member 12 includes one or more solid and/or slotted tubular members, and one or more of the solid and/or slotted tubular members include resilient sealing members coupled to the exterior surfaces of the solid and/or slotted tubular members for engaging the wellbore 30 and/or one or more preexisting wellbore casings coupled to the wellbore. In an exemplary embodiment, the tubular support members, 14, 18, 22, and 26 define corresponding passages, that may or may not be valveable, for conveying fluidic materials into and/or through the apparatus 10.

In an exemplary embodiment, the locking device 16 includes one or more conventional controllable locking devices such as, for example, slips and/or dogs for controllably engaging the tubular member 12. In an exemplary embodiment, the locking device 16 is controlled by injecting fluidic materials into the locking device.

In an exemplary embodiment, the actuator 20 is a conventional actuator that is adapted to displaced the adjustable expansion mandrel 24 and float shoe 28 upwardly or downwardly relative to the actuator.

In an exemplary embodiment, the adjustable expansion mandrel 24 is a conventional adjustable expansion mandrel that may be expanded to a larger outside dimension or collapsed to a smaller outside dimension and includes external surfaces for engaging the tubular member 12 to thereby radially expand and plastically deform the tubular member when the adjustable expansion mandrel is expanded to the larger outside dimension. In an alternative embodiment, the adjustable expansion mandrel 24 may include a rotary adjustable expansion device such as, for example, the commercially available rotary expansion devices of Weatherford International, Inc. In several alternative embodiments, the cross sectional profile of the adjustable expansion mandrel 24 for radial expansion operations may, for example, be an n-sided shape, where n may vary from 2 to infinity, and the side shapes may include straight line segments, arcuate segments, parabolic segments, and/or hyperbolic segments. In several alternative embodiments, the cross sectional profile of the adjustable expansion mandrel 24 may, for example, be circular, oval, elliptical, and/or multifaceted.

In an exemplary embodiment, the float shoe 28 is a conventional float shoe.

In an exemplary embodiment, the apparatus 10 is positioned within a preexisting structure 30 such as, for example, a wellbore that traverses a subterranean formation 32. The wellbore 30 may have any orientation from vertical to horizontal. In several exemplary embodiments, the wellbore 30 may include one or more preexisting solid and/or slotted and/or perforated wellbore casings that may or may not overlap with one another within the wellbore.

As illustrated in Fig. 2, the adjustable expansion mandrel 24 and the float shoe 28 are then displaced downwardly out of the tubular member 12 by the actuator 20. During the downward displacement of the adjustable expansion mandrel 24 and the float shoe 28 out of the tubular member 12, the tubular member is maintained in a stationary position relative to the tubular support member 14 by the locking device 16.

As illustrated in Fig. 3, the adjustable expansion mandrel 24 is then expanded to the larger dimension. In several alternative embodiments, the adjustable expansion mandrel 24 may be expanded to the larger dimension by, for example, injecting a fluidic material into the adjustable expansion mandrel and/or by impacting the float shoe 28 on the bottom of the wellbore 30. After expanding the adjustable expansion mandrel 24 to the larger dimension, expansion surfaces 24a are defined on the

adjustable expansion mandrel that may include, for example, conical, spherical, elliptical, and/or hyperbolic surfaces for radially expanding and plastically deforming the tubular member 12. In an exemplary embodiment, the expansion surfaces 24a also include means for lubricating the interface between the expansion surfaces and the tubular member 12 during the radial expansion and plastic deformation of the tubular member.

As illustrated in Fig. 4, the adjustable expansion mandrel 24 is then displaced upwardly by the actuator 20 to thereby radially expand and plastically deform a portion of the tubular member 12. In an exemplary embodiment, during the upward displacement of the adjustable expansion mandrel 24, the tubular member 12 is maintained in a stationary position relative to the tubular support member 14 by the locking device 16. In an exemplary embodiment, the tubular member 12 is radially expanded and plastically deformed into engagement with the wellbore 30 and/or one or more preexisting wellbore casings coupled to the wellbore 30. In an exemplary embodiment, the interface between the expansion surfaces 24a of the adjustable expansion mandrel 24 and the tubular member 12 is not fluid tight in order to facilitate the lubrication of the interface between the expansion surface of the adjustable expansion mandrel and the tubular member.

As illustrated in Fig. 5, the locking device 16 is then disengaged from the tubular member 12, and the tubular member 12 is supported by the adjustable expansion mandrel 24. The tubular support member 14, the locking device 16, the tubular support member 18, and the actuator 20 are then displaced upwardly relative to the adjustable expansion mandrel 24.

As illustrated in Fig. 6, the locking device 16 then engages the tubular member 12 to maintain the tubular member in a stationary position relative to the tubular support member 14, and the adjustable expansion mandrel 24 is displaced upwardly relative by the actuator 20 to radially expand and plastically deform another portion of the tubular member.

In an exemplary embodiment, the operations of Figs. 5 and 6 are then repeated until the entire length of the tubular member 12 is radially expanded and plastically deformed by the adjustable expansion mandrel 24. In several alternative embodiments, the adjustable expansion mandrel 24 may be collapsed to the smaller

dimension prior to the further, or complete, radial expansion and plastic deformation of the tubular member 12.

In several alternative embodiments, as illustrated in Fig. 6a, the apparatus 10 further includes one or more cup seals 34 that are coupled to the tubular support member 22 and engage the tubular member 12 to define an annular chamber 36 above the adjustable expansion cone 24, and fluidic materials 38 are injected into the tubular member 12 through passages defined within the tubular support member 14, the locking device 16, the tubular support member 18, the actuator 20, the tubular support member 22, the adjustable expansion mandrel 24, the tubular support member 26, and the float shoe 28 to thereby pressurize the annular chamber 36. In this manner, the resulting pressure differential created across the cup seals 34 causes the cup seals to pull the adjustable expansion mandrel 24 upwardly to radially expand and plastically deform the tubular member 12. In several alternative embodiments, the injection of the fluidic material 38 into the tubular member 12 is provided in combination with, or in the alternative to, the upward displacement of the expansion mandrel 24 by the actuator 20. In several alternative embodiments, during the injection of the fluidic material 38, the locking device 16 is disengaged from the tubular member 12.

Referring to Fig. 7, an alternative embodiment of an apparatus 100 for radially expanding and plastically deforming the tubular member 12 is substantially identical in design and operation to the apparatus 10 with the addition of one or more conventional drilling members 40a-40b that are pivotally coupled to the float shoe 28. During operation of the apparatus 100, the drilling members 40a-40b may be operated to extend the length and/or diameter of the wellbore 30, for example, by rotating the apparatus and/or by injecting fluidic materials into the apparatus to operate the drilling members.

As illustrated in Fig. 7, in an exemplary embodiment, the apparatus 100 is initially positioned within the preexisting structure 30.

As illustrated in Fig. 8, in an exemplary embodiment, the drilling members 40a-40b may then be pivoted inwardly in a conventional manner.

As illustrated in Fig. 9 the adjustable expansion mandrel 24, the float shoe 28, and the drilling members 40a-40b are then displaced downwardly out of the tubular member 12 by the actuator 20. During the downward displacement of the adjustable expansion mandrel 24, the float shoe 28, and the drilling members 40a-40b out of the

tubular member 12, the tubular member is maintained in a stationary position relative to the tubular support member 14 by the locking device 16.

As illustrated in Fig. 10, the adjustable expansion mandrel 24 is then expanded to the larger dimension. In several alternative embodiments, the adjustable expansion mandrel 24 may be expanded to the larger dimension by, for example, injecting a fluidic material into the adjustable expansion mandrel and/or by impacting the drilling members 40a-40b on the bottom of the wellbore 30. After expanding the adjustable expansion mandrel 24 to the larger dimension, expansion surfaces 24a are defined on the adjustable expansion mandrel that may include, for example, conical, spherical, elliptical, and/or hyperbolic surfaces for radially expanding and plastically deforming the tubular member 12. In an exemplary embodiment, the expansion surfaces 24a also include means for lubricating the interface between the expansion surfaces and the tubular member 12 during the radial expansion and plastic deformation of the tubular member.

As illustrated in Fig. 11, the adjustable expansion mandrel 24 is then displaced upwardly by the actuator 20 to thereby radially expand and plastically deform a portion of the tubular member 12. In an exemplary embodiment, during the upward displacement of the adjustable expansion mandrel 24, the tubular member 12 is maintained in a stationary position relative to the tubular support member 14 by the locking device 16. In an exemplary embodiment, the tubular member 12 is radially expanded and plastically deformed into engagement with the wellbore 30 and/or one or more preexisting wellbore casings coupled to the wellbore 30. In an exemplary embodiment, the interface between the expansion surfaces 24a of the adjustable expansion mandrel 24 and the tubular member 12 is not fluid tight in order to facilitate the lubrication of the interface between the expansion surface of the adjustable expansion mandrel and the tubular member.

As illustrated in Fig. 12, the locking device 16 is then disengaged from the tubular member 12, and the tubular member 12 is supported by the adjustable expansion mandrel 24. The tubular support member 14, the locking device 16, the tubular support member 18, and the actuator 20 are then displaced upwardly relative to the adjustable expansion mandrel 24.

As illustrated in Fig. 13, the locking device 16 then engages the tubular member 12 to maintain the tubular member in a stationary position relative to the tubular

support member 14, and the adjustable expansion mandrel 24 is displaced upwardly relative by the actuator 20 to radially expand and plastically deform another portion of the tubular member.

In an exemplary embodiment, the operations of Figs. 12 and 13 are then repeated until the entire length of the tubular member 12 is radially expanded and plastically deformed by the adjustable expansion mandrel 24. In several alternative embodiments, the adjustable expansion mandrel 24 may be collapsed to the smaller dimension prior to the further, or complete, radial expansion and plastic deformation of the tubular member 12.

Referring to Fig. 14, an alternative embodiment of an apparatus 200 for radially expanding and plastically deforming the tubular member 12 is substantially identical in design and operation to the apparatus 10 except that the adjustable expansion mandrel 24 has been replaced by an upper adjustable expansion mandrel 202 that is coupled to the tubular support member 22, a tubular support member 204 that is coupled to the upper adjustable expansion mandrel, and a lower adjustable expansion mandrel 206 that is coupled to the tubular support member 204 and the tubular support member 26.

The upper and lower adjustable expansion mandrels, 202 and 206, may be conventional adjustable expansion mandrels that may be expanded to larger outside dimensions or collapsed to smaller outside dimensions and include external surfaces for engaging the tubular member 12 to thereby radially expand and plastically deform the tubular member when the adjustable expansion mandrels are expanded to the larger outside dimensions. In an alternative embodiment, the upper and/or lower adjustable expansion mandrels, 202 and 206, may include rotary adjustable expansion devices such as, for example, the commercially available rotary expansion devices of Weatherford International, Inc. In an exemplary embodiment, the tubular support member 204 defines a passage, that may, or may not, be valveable, for conveying fluidic materials into and/or through the apparatus 200. In several alternative embodiments, the cross sectional profiles of the adjustable expansion mandrels, 202 and 206, for radial expansion operations may, for example, be n-sided shapes, where n may vary from 2 to infinity, and the side shapes may include straight line segments, arcuate segments, parabolic segments, and/or hyperbolic segments. In several alternative embodiments, the cross sectional profiles of the adjustable expansion

mandrels, 202 and 206, may, for example, be circular, oval, elliptical, and/or multifaceted.

As illustrated in Fig. 14, in an exemplary embodiment, the apparatus 200 is initially positioned within the preexisting structure 30.

As illustrated in Fig. 15, the lower adjustable expansion mandrel 206 and the float shoe 28 are then displaced downwardly out of the tubular member 12 by the actuator 20. During the downward displacement of the lower adjustable expansion mandrel 206 and the float shoe 28 out of the tubular member 12, the tubular member is maintained in a stationary position relative to the tubular support member 14 by the locking device 16.

As illustrated in Fig. 16, the lower adjustable expansion mandrel 206 is then expanded to the larger dimension. In several alternative embodiments, the lower adjustable expansion mandrel 206 may be expanded to the larger dimension by, for example, injecting a fluidic material into the lower adjustable expansion mandrel and/or by impacting the float shoe 28 on the bottom of the wellbore 30. After expanding the lower adjustable expansion mandrel 206 to the larger dimension, expansion surfaces 206a are defined on the lower adjustable expansion mandrel that may include, for example, conical, spherical, elliptical, and/or hyperbolic surfaces for radially expanding and plastically deforming the tubular member 12. In an exemplary embodiment, the expansion surfaces 206a also include means for lubricating the interface between the expansion surfaces and the tubular member 12 during the radial expansion and plastic deformation of the tubular member.

As illustrated in Fig. 17, the lower adjustable expansion mandrel 206 is then displaced upwardly by the actuator 20 to thereby radially expand and plastically deform a portion 12a of the tubular member 12. In an exemplary embodiment, during the upward displacement of the lower adjustable expansion mandrel 206, the tubular member 12 is maintained in a stationary position relative to the tubular support member 14 by the locking device 16. In an exemplary embodiment, the tubular member 12 is radially expanded and plastically deformed into engagement with the wellbore 30 and/or one or more preexisting wellbore casings coupled to the wellbore 30. In an exemplary embodiment, the interface between the expansion surfaces 206a of the lower adjustable expansion mandrel 206 and the tubular member 12 is not fluid tight in order to facilitate the lubrication of the interface between the expansion surface of the

lower adjustable expansion mandrel and the tubular member. In an exemplary embodiment, the expansion surfaces 206a also include means for lubricating the interface between the expansion surfaces and the tubular member 12 during the radial expansion and plastic deformation of the tubular member.

As illustrated in Fig. 18, the upper and lower adjustable expansion mandrels, 202 and 206, and the float shoe 28 are then displaced downwardly by the actuator 20. During the downward displacement of the upper and lower adjustable expansion mandrels, 202 and 206, and the float shoe 28, the tubular member is maintained in a stationary position relative to the tubular support member 14 by the locking device 16.

As illustrated in Fig. 19, the upper adjustable expansion mandrel 202 is then expanded to the larger dimension and the lower adjustable expansion mandrel 206 is collapsed to the smaller dimension. In an exemplary embodiment, the larger dimension of the upper adjustable expansion mandrel 202 is less than the larger dimension of the lower adjustable expansion mandrel 206. In several alternative embodiments, the upper adjustable expansion mandrel 202 may be expanded to the larger dimension and the lower adjustable expansion mandrel 206 may be collapsed to the smaller dimension by, for example, injecting fluidic material into the upper and/or adjustable expansion mandrel and/or by impacting the float shoe 28 on the bottom of the wellbore 30. After expanding the upper adjustable expansion mandrel 202 to the larger dimension, expansion surfaces 202a are defined on the upper adjustable expansion mandrel that may include, for example, conical, spherical, elliptical, and/or hyperbolic surfaces for radially expanding and plastically deforming the tubular member 12. In an exemplary embodiment, the expansion surfaces 202a also include means for lubricating the interface between the expansion surfaces and the tubular member 12 during the radial expansion and plastic deformation of the tubular member.

As illustrated in Fig. 20, the upper adjustable expansion mandrel 202 is then displaced upwardly by the actuator 20 to thereby radially expand and plastically deform a portion 12b of the tubular member 12 above the portion 12a of the tubular member. In an exemplary embodiment, the inside diameter of the radially expanded and plastically deformed portion 12a of the tubular member 12 is greater than the inside diameter of the radially expanded and plastically deformed portion 12b of the tubular member. In an exemplary embodiment, during the upward displacement of the upper adjustable expansion mandrel 202, the tubular member 12 is maintained in a stationary

position relative to the tubular support member 14 by the locking device 16. In an exemplary embodiment, the tubular member 12 is radially expanded and plastically deformed into engagement with the wellbore 30 and/or one or more preexisting wellbore casings coupled to the wellbore 30. In an exemplary embodiment, the interface between the expansion surfaces 202a of the upper adjustable expansion mandrel 202 and the tubular member 12 is not fluid tight in order to facilitate the lubrication of the interface between the expansion surface of the upper adjustable expansion mandrel and the tubular member.

As illustrated in Fig. 21, the locking device 16 is then disengaged from the tubular member 12, and the tubular member 12 is supported by the upper adjustable expansion mandrel 202. The tubular support member 14, the locking device 16, the tubular support member 18, and the actuator 20 are then displaced upwardly relative to the upper adjustable expansion mandrel 202 and the tubular member 12.

As illustrated in Fig. 22, the locking device 16 then engages the tubular member 12 to maintain the tubular member in a stationary position relative to the tubular support member 14, and the upper adjustable expansion mandrel 202 is displaced upwardly relative by the actuator 20 to radially expand and plastically deform the portion 12b of the tubular member.

In an exemplary embodiment, the operations of Figs. 21 and 22 are then repeated until the remaining length of the portion 12b of the tubular member 12 is radially expanded and plastically deformed by the upper adjustable expansion mandrel 202. In several alternative embodiments, the upper adjustable expansion mandrel 202 may be collapsed to the smaller dimension prior to the further, or complete, radial expansion and plastic deformation of the tubular member 12.

Referring to Fig. 23, in an exemplary embodiment, the method and apparatus of one or more of Figs. 1-22 are repeated to provide a mono diameter wellbore casing 300 within a borehole 302 that traverses a subterranean formation 304 by successively overlapping and radially expanding and plastically deforming wellbore casing 306a-306d within the wellbore. In this manner, a wellbore casing 300 is provided that defines an interior passage having a substantially constant cross sectional area throughout its length. In several alternative embodiments, the cross section of the wellbore casing 300 may be, for example, square, rectangular, elliptical, oval, circular and/or faceted.

Referring to Figs. 24a-24k, an exemplary embodiment of an apparatus 400 for radially expanding and plastically deforming a tubular member includes a tubular support member 402 that defines a longitudinal passage 402a that is threadably coupled to and received within an end of a tool joint adaptor 404 that defines a longitudinal passage 404a and radial passages 404b and 404c.

The other end of the tool joint adaptor 404 receives and is threadably coupled to an end of a gripper upper mandrel 406 that defines a longitudinal passage 406a, external radial mounting holes, 406b and 406c, an external annular recess 406d, an external annular recess 406e, hydraulic port 406f, an internal annular recess 406g, hydraulic port 406h, external radial mounting holes, 406i and 406j, and includes a flange 406k, and a flange 406l. Torsional locking pins, 408a and 408b, are coupled to the external radial mounting holes, 406b and 406c, respectively, of the gripper upper mandrel 406 and received within the radial passages, 404b and 404c, respectively, of the tool joint adaptor 404.

A spring retainer sleeve 410 that includes a flange 410a receives and is threadably coupled to the gripper upper mandrel 406 between an end face of the tool joint adaptor 404 and the flange 406k of the gripper upper mandrel. A bypass valve body 412 receives and is movably coupled to the gripper upper mandrel 406 that defines radial passages, 412a and 412b, and an internal annular recess 412c includes a flange 412d.

An end of a spring cover 414 receives and is movably coupled to the spring retainer sleeve 410 that defines an internal annular recess 414a. The other end of the spring cover 414 receives and is threadably coupled to an end of the bypass valve body 412. A spring guide 416, a spring 418, and a spring guide 420 are positioned within an annular chamber 422 defined between the spring cover 414 and the flange 406k of the gripper upper mandrel 406. Furthermore, an end of the spring guide 416 abuts an end face of the spring retainer sleeve 410.

Casing gripper locking dogs, 424a and 424b, are received and pivotally mounted within the radial passages, 412a and 412b, respectively, of the bypass valve body 412. An end of each of the casing gripper locking dogs, 424a and 424b, engage and are received within the outer annular recess 406d of the gripper upper mandrel 406. An end of a debris trap 426 receives and is threadably coupled to an end of the bypass

valve body 412, and the other end of the debris trap receives and is movably coupled to the flange 406l of the gripper upper mandrel 406.

An end of a gripper body 428 receives and is threadably coupled to an end of the gripper upper mandrel 406 that defines a longitudinal passage 428a, radial passages, 428b and 428c, radial slip mounting passages, 428d-428m, and radial passages, 428n and 428o, includes a flange 428p.

Hydraulic slip pistons 432a-432j are movably mounted with the radial slip mounting passages 428d-428m, respectively, for movement in the radial direction. Retainers 434a-434j are coupled to the exterior of the flange 428p of the gripper body 428 for limiting the outward radial movement of the hydraulic slip pistons 432a-432j, respectively, and springs 436a-436j are positioned within the radial slip mounting passages, 428d-428m, respectively, of the gripper body between the hydraulic slip pistons, 432a-432j, and the retainers, 434a-434j, respectively. During operation of the apparatus 400, pressurization of the radial slip mounting passages, 428d-428m, displaces the hydraulic slip pistons, 432a-432j, respectively, radially outwardly and compresses the springs, 436a-436j, respectively, and during depressurization of the radial slip mounting passages, 428d-428m, springs, 436a-436j, respectively, displace the hydraulic slip pistons, 432a-432j, inwardly. In an exemplary embodiment, displacement of the hydraulic slip pistons 432a-432j radially outwardly permits at least portions of the hydraulic slip pistons to engage and grip an outer tubular member.

Torsional locking pins, 438a and 438b, are coupled to the external radial mounting holes, 406i and 406j, respectively, of the gripper upper mandrel 406 and received within the radial passages, 428b and 428c, respectively, of the gripper body 428.

An end of a gripper body 440 receives and is threadably coupled to an end of the gripper body 428 that defines a longitudinal passage 440a, radial passages, 440b and 440c, radial slip mounting passages, 440d-440m, and radial passages, 440n and 440o, includes a flange 440p.

Hydraulic slip pistons 442a-442j are movably mounted with the radial slip mounting passages 440d-440m, respectively, for movement in the radial direction. Retainers 444a-444j are coupled to the exterior of the flange 440p of the gripper body 440 for limiting the outward radial movement of the hydraulic slip pistons 442a-442j, respectively, and springs 446a-446j are positioned within the radial slip mounting

passages, 440d-440m, respectively, of the gripper body between the hydraulic slip pistons, 442a-442j, and the retainers, 444a-444j, respectively. During operation of the apparatus 400, pressurization of the radial slip mounting passages, 440d-440m, displaces the hydraulic slip pistons, 442a-442j, respectively, radially outwardly and compresses the springs, 446a-446j, respectively, and during depressurization of the radial slip mounting passages, 440d-440m, the springs, 446a-446j, respectively, displace the hydraulic slip pistons, 442a-442j, radially inward. In an exemplary embodiment, displacement of the hydraulic slip pistons 442a-442j radially outwardly permits at least portions of the hydraulic slip pistons to engage and grip an outer tubular member.

Torsional locking pins, 448a and 448b, are coupled to the external radial mounting holes, 428n and 428o, respectively, of the gripper body 428 and received within the radial passages, 440b and 440c, respectively, of the gripper body 440.

An end of a tool joint adaptor 450 that defines a longitudinal passage 450a, radial passages, 450b and 450c, and an inner annular recess 450d, receives and is threadably coupled to an end of the gripper body 440. Torsional locking pins, 452a and 452b, are coupled to the external radial mounting holes, 440n and 440o, respectively, of the gripper body 428 and received within the radial passages, 450b and 450c, respectively, of the tool joint adaptor 450.

A bypass tube 454 that defines a longitudinal passage 454a is received within the longitudinal passages, 406a, 428a, 440a, and 450a, of the gripper upper mandrel 406, the gripper body 428, the gripper body 440, and the tool joint adaptor 450, respectively, is coupled to the recess 406g of the gripper upper mandrel at one end and is coupled to the recess 450d of the tool joint adaptor at the other end.

An end of a cross over adaptor 456 that defines a longitudinal passage 456a receives and is threadably coupled to an end of the tool joint adaptor 450. The other end of the cross over adaptor 456 is received within and is coupled to an end of a tool joint adaptor 458 that defines a longitudinal passage 458a and external radial mounting holes, 458b and 458c.

An end of a positive casing locking body 460 that defines a tapered longitudinal passage 460a and radial passages, 460b and 460c, receives and is threadably coupled to the other end of the tool joint adaptor 458. Torsional locking pins, 462a and 462b, are coupled to the external radial mounting holes, 458b and 458c, respectively, of the

tool joint adaptor 458 and received within the radial passages, 460b and 460c, respectively, of the positive casing locking body 460.

An end of a positive casing locking dog 464 mates with, is received within, and is coupled to the other end of the positive casing locking body 460 that includes internal flanges, 464a and 464b, and an external flange 464c. In an exemplary embodiment, the external flange 464c of the positive casing locking dog 464 includes an ribbed external surface 464d that engages and locks onto a ribbed internal surface 466a of a positive casing locking collar 466.

One end of the positive casing locking collar 466 is threadably coupled to a casing 468 and the other end of the positive casing locking collar is threadably coupled to a casing 470 that defines radial mounting holes, 470a and 470b, at a lower end thereof. In this manner, the casings, 468 and 470, are also engaged by and locked onto the positive casing locking dog 464.

The other end of the positive casing locking dog 464 mates with, is received within, and is coupled to an end of a positive casing locking body 472 that defines a tapered longitudinal passage 472a and radial passages, 472b and 472c. The other end of the positive casing locking body 472 receives, mates with, and is coupled to an end of a casing lock barrel adaptor 474 that defines external radial mounting holes, 474a and 474b, and external radial mounting holes, 474c and 474d. Torsional locking pins, 475a and 475b, are coupled to the external radial mounting holes, 474a and 474b, respectively, of the casing lock barrel adaptor 474 and received within the radial passages, 472b and 472c, respectively, of the positive casing locking body 472.

An end of a positive casing lock releasing mandrel 476 that defines a longitudinal passage 476a, an external annular recess 476b, an external annular recess 476c, an external annular recess 476d, and an external annular recessed end portion 476e, is received within and movably coupled to an end of the tool joint adaptor 458. The middle portion of the positive casing lock releasing mandrel 476 is received within and mates with the internal flanges, 464a and 464b, of the positive casing locking dogs 464. The other end of the positive casing lock releasing mandrel 476 is received within and is movably coupled to the end of the casing lock barrel adaptor 474, and the external annular recessed portion 476e of the positive casing lock releasing mandrel is threadably coupled to and received within an end of a positive casing lock lower

mandrel 478 that defines a longitudinal passage 478a, external radial mounting holes, 478b and 478c, and an external annular recessed end portion 478d.

A shear pin ring 480 that defines radial passages, 480a and 480b, receives and mates with the positive casing lock lower mandrel 478. Shear pins, 482a and 482b, are coupled to the external radial mounting holes, 478b and 478c, respectively, of the positive casing lock lower mandrel 478 and are received within the radial passages, 480a and 480b, respectively, of the shear pin ring 480.

An end of an actuator barrel 484 that defines a longitudinal passage 484a, radial passages, 484b and 484c, and radial passages, 484d and 484e, is threadably coupled to an end of the casing lock barrel adaptor 474. Torsional locking pins, 486a and 486b, are coupled to the external radial mounting holes, 474c and 474d, respectively, of the casing lock barrel adaptor and are received within the radial passages, 484b and 484c, respectively, of the actuator barrel.

The other end of the actuator barrel 484 is threadably coupled to an end of a barrel connector 486 that defines an internal annular recess 486a, external radial mounting holes, 486b and 486c, radial passages, 486d and 486e, and external radial mounting holes, 486f and 486g. A sealing cartridge 488 is received within and coupled to the internal annular recess 486a of the barrel connector 486 for fluidicly sealing the interface between the barrel connector and the sealing cartridge. Torsional locking pins, 490a and 490b, are coupled to and mounted within the external radial mounting holes, 486b and 486c, respectively, of the barrel connector 486 and received within the radial passages, 484d and 484e, of the actuator barrel 484.

The other end of the barrel connector 486 is threadably coupled to an end of an actuator barrel 492 that defines a longitudinal passage 492a, radial passages, 492b and 492c, and radial passages, 492d and 492e. Torsional locking pins, 494a and 494b, are coupled to and mounted within the external radial mounting holes, 486f and 486g, respectively, of the barrel connector 486 and received within the radial passages, 492b and 492c, of the actuator barrel 492. The other end of the actuator barrel 492 is threadably coupled to an end of a barrel connector 496 that defines an internal annular recess 496a, external radial mounting holes, 496b and 496c, radial passages, 496d and 496e, and external radial mounting holes, 496f and 496g. A sealing cartridge 498 is received within and coupled to the internal annular recess 496a of the barrel connector 496 for fluidicly sealing the interface between the barrel connector and the

sealing cartridge. Torsional locking pins, 500a and 500b, are coupled to and mounted within the external radial mounting holes, 496b and 496c, respectively, of the barrel connector 496 and received within the radial passages, 492d and 492e, of the actuator barrel 492.

The end of the barrel connector 496 is threadably coupled to an end of an actuator barrel 502 that defines a longitudinal passage 502a, radial passages, 502b and 502c, and radial passages, 502d and 502e. Torsional locking pins, 504a and 504b, are coupled to and mounted within the external radial mounting holes, 496f and 496g, respectively, of the barrel connector 496 and received within the radial passages, 502b and 502c, of the actuator barrel 502. The other end of the actuator barrel 502 is threadably coupled to an end of a barrel connector 506 that defines an internal annular recess 506a, external radial mounting holes, 506b and 506c, radial passages, 506d and 506e, and external radial mounting holes, 506f and 506g. Torsional locking pins, 508a and 508b, are coupled to and mounted within the external radial mounting holes, 506b and 506c, respectively, of the barrel connector 506 and received within the radial passages, 502d and 502e, of the actuator barrel 502. A sealing cartridge 510 is received within and coupled to the internal annular recess 506a of the barrel connector 506 for fluidicly sealing the interface between the barrel connector and the sealing cartridge.

The other end of the barrel connector 506 is threadably coupled to an end of an actuator barrel 512 that defines a longitudinal passage 512a, radial passages, 512b and 512c, and radial passages, 512d and 512e. Torsional locking pins, 514a and 514b, are coupled to and mounted within the external radial mounting holes, 506f and 506g, respectively, of the barrel connector 506 and received within the radial passages, 512b and 512c, of the actuator barrel 512. The other end of the actuator barrel 512 is threadably coupled to an end of a lower stop 516 that defines an internal annular recess 516a, external radial mounting holes, 516b and 516c, and an internal annular recess 516d that includes one or more circumferentially spaced apart locking teeth 516e at one end and one or more circumferentially spaced apart locking teeth 516f at the other end. A sealing cartridge 518 is received within and coupled to the internal annular recess 516a of the barrel connector 516 for fluidicly sealing the interface between the barrel connector and the sealing cartridge. Torsional locking pins, 520a and 520b, are coupled to and mounted within the external radial mounting holes, 516b

and 516c, respectively, of the barrel connector 516 and received within the radial passages, 512d and 512e, of the actuator barrel 512.

A connector tube 522 that defines a longitudinal passage 522a is received within and sealingly and movably engages the interior surface of the sealing cartridge 488 mounted within the annular recess 486a of the barrel connector 486. In this manner, during longitudinal displacement of the connector tube 522 relative to the barrel connector 486, a fluidic seal is maintained between the exterior surface of the connector tube and the interior surface of the barrel connector. An end of the connector tube 522 is received within and is threadably coupled to an end of dart/ball guide 524 that defines a tapered passage 524a at the other end.

The other end of the connector tube 522 is received within and threadably coupled to an end of a piston 526 that defines a longitudinal passage 526a and radial passages, 526b and 526c, that includes a flange 526d at one end. A sealing cartridge 528 is mounted onto and sealingly coupled to the exterior of the piston 526 proximate the flange 526d. The sealing cartridge 528 also mates with and sealingly engages the interior surface of the actuator barrel 492. In this manner, during longitudinal displacement of the piston 526 relative to the actuator barrel 492, a fluidic seal is maintained between the exterior surface of the piston and the interior surface of the actuator barrel.

The other end of the piston 526 receives and is threadably coupled to an end of a connector tube 529 that defines a longitudinal passage 528a. The connector tube 529 is received within and sealingly and movably engages the interior surface of the sealing cartridge 498 mounted within the annular recess 496a of the barrel connector 496. In this manner, during longitudinal displacement of the connector tube 529 relative to the barrel connector 496, a fluidic seal is maintained between the exterior surface of the connector tube and the interior surface of the barrel connector.

The other end of the connector tube 529 is received within and threadably coupled to an end of a piston 530 that defines a longitudinal passage 530a and radial passages, 530b and 530c, that includes a flange 530d at one end. A sealing cartridge 532 is mounted onto and sealingly coupled to the exterior of the piston 530 proximate the flange 530d. The sealing cartridge 532 also mates with and sealingly engages the interior surface of the actuator barrel 502. In this manner, during longitudinal displacement of the piston 530 relative to the actuator barrel 502, a fluidic seal is

maintained between the exterior surface of the piston and the interior surface of the actuator barrel.

The other end of the piston 530 receives and is threadably coupled to an end of a connector tube 534 that defines a longitudinal passage 534a. The connector tube 534 is received within and sealingly and movably engages the interior surface of the sealing cartridge 510 mounted within the annular recess 506a of the barrel connector 506. In this manner, during longitudinal displacement of the connector tube 534 relative to the barrel connector 506, a fluidic seal is maintained between the exterior surface of the connector tube and the interior surface of the barrel connector.

The other end of the connector tube 534 is received within and threadably coupled to an end of a piston 536 that defines a longitudinal passage 536a, radial passages, 536b and 536c, and external radial mounting holes, 536d and 536e, that includes a flange 536f at one end. A sealing cartridge 538 is mounted onto and sealingly coupled to the exterior of the piston 536 proximate the flange 536d. The sealing cartridge 538 also mates with and sealingly engages the interior surface of the actuator barrel 512. In this manner, during longitudinal displacement of the piston 536 relative to the actuator barrel 512, a fluidic seal is maintained between the exterior surface of the piston and the interior surface of the actuator barrel.

The other end of the piston 536 is received within and threadably coupled to an end of a lock nut 540 that defines radial passages, 540a and 540b, and includes one or more circumferentially spaced apart locking teeth 540c at the other end for engaging the circumferentially spaced apart locking teeth 516e of the lower stop 516.

A threaded bushing 542 is received within and threadably coupled to the circumferentially spaced apart locking teeth 540c of the lock nut 540. An end of a connector tube 544 that defines a longitudinal passage 544a is received within and is threadably coupled to the threaded bushing 542. A sealing sleeve 546 is received within and is threadably coupled to adjacent ends of the piston 536 and the connector tube 544 for fluidicly sealing the interface between the end of the piston and the end of the connector tube. Torsional locking pins, 548a and 548b, are mounted within and coupled to the external radial mounting holes, 536d and 536e, respectively, of the piston 536 that are received within the radial passages, 540a and 540b, of the stop nut 540.

The connector tube 544 is received within and sealingly and movably engages the interior surface of the sealing cartridge 518 mounted within the annular recess 516a of the barrel connector 516. In this manner, during longitudinal displacement of the connector tube 544 relative to the barrel connector 516, a fluidic seal is maintained between the exterior surface of the connector tube and the interior surface of the barrel connector.

The other end of the connector tube 544 is received within and is threadably coupled to a threaded bushing 550. The threaded bushing 550 is received within and threadably coupled to a lock nut 552 that defines radial passages, 552a and 552b, and includes one or more circumferentially spaced apart locking teeth 552c at one end for engaging the circumferentially spaced apart locking teeth 516f of the lower stop 516. The other end of the lock nut 552 receives and is threadably coupled to an end of tool joint adaptor 554 that defines a longitudinal passage 554a, external radial mounting holes, 554b and 554c. Torsional locking pins, 556a and 556b, are mounted within and coupled to the external radial mounting holes, 554b and 554c, respectively, of the tool joint adaptor 554 that are received within the radial passages, 552a and 552b, of the stop nut 552. A sealing sleeve 558 is received within and is threadably coupled to adjacent ends of the connector tube 544 and the tool joint adaptor 554 for fluidicly sealing the interface between the end of the connector tube and the end of the tool joint adaptor.

The other end of the tool joint adaptor 554 is received within and threadably coupled to an end of a tool joint adaptor 560 that defines a longitudinal passage 560a. A torsion plate 562 is received within and threadably coupled to the other end of the tool joint adaptor 560 that defines a longitudinal passage 562a and includes one or more circumferentially spaced apart locking teeth 562b at one end. An end of an upper bushing 564 is also received within and threadably coupled to the other end of the tool joint adaptor 560 proximate the torsion plate 562 that receives and is threadably coupled to an end of a cup mandrel 566 that defines a longitudinal passage 566a and includes a plurality of circumferentially spaced apart locking teeth 566b at one end for engaging the circumferentially spaced apart locking teeth 562b of the torsion plate 562. The end of the cup mandrel 566 is further positioned proximate an end face of the torsion plate 562.

A thimble 568 is mounted on and is threadably coupled to the cup mandrel 566 proximate an end face of the upper bushing 564. An inner thimble 570 is mounted on and is threadably coupled to the cup mandrel 566 proximate an end of the thimble 568, and one end of the inner thimble is received within and mates with the end of the thimble. A resilient packer cup 572 is mounted on and sealingly engages the cup mandrel 566 proximate an end of the inner thimble 570, and one end of the packer cup is received within and mates with the end of the inner thimble. A packer cup backup ring 574 is mounted on the inner thimble 570 proximate an end face of the thimble 568, and an end of the packer cup backup ring 574 receives and mates with the packer cup 572. A spacer 576 is mounted on and threadably engages the cup mandrel 566 proximate an end face of the packer cup 572.

A thimble 578 is mounted on and is threadably coupled to the cup mandrel 566 proximate an end of the spacer 576. An inner thimble 580 is mounted on and is threadably coupled to the cup mandrel 566 proximate an end of the thimble 578, and one end of the inner thimble is received within and mates with the end of the thimble. A resilient packer cup 582 is mounted on and sealingly engages the cup mandrel 566 proximate an end of the inner thimble 580, and one end of the packer cup is received within and mates with the end of the inner thimble. A packer cup backup ring 584 is mounted on the inner thimble 580 proximate an end face of the thimble 578, and an end of the packer cup backup ring 584 receives and mates with the packer cup 582. An adjustable spacer 586 is mounted on and threadably engages the cup mandrel 566 proximate an end face of the packer cup 582.

An end of a cone mandrel 588 that defines a longitudinal passage 588a, an external lock ring groove 588b, an external lock ring groove 588c, an external lock ring groove 588d, an external lock ring groove 588e, radial passages, 588f and 588g, and locking dog grooves 588h receives and is threadably coupled to an end of the cup mandrel 566. A shear pin bushing 590 that defines external radial mounting holes, 590a and 590b, at one end and an annular recess 590c at another end and includes circumferentially spaced apart locking teeth 590d at the other end is mounted on and is movably coupled to the cone mandrel 588. Torsional shear pins, 592a and 592b, are mounted within and coupled to the external radial mounting holes, 590a and 590b, respectively, of the shear pin bushing 590 and received within the radial passages, 470a and 470b, respectively, of the end of the casing 470. In this manner, torque loads

may be transmitted between the casing 470 and the shear pin bushing 590. A resilient lock ring 594 is retained in the external lock ring groove 588b of the cone mandrel and received within the internal annular recess 590c at the end of the shear pin bushing 590.

Referring to Figs. 24j, 25a, and 25b, an upper cone retainer 596 receives, mates with, and is coupled to the end of the shear pin bushing 590 that includes an internal flange 596a and an internal upper pivot point flange 596b. An end of an upper cam 598 includes a tubular base 598a that mates with, receives, and is movably coupled to the cone mandrel 588. The tubular base 598a of the upper cam 598 further includes an external flange 598b that is received within and mates with the upper cone retainer 596 proximate the internal flange 596a of the upper cone retainer and a plurality of circumferentially spaced apart locking teeth 598c that engage the circumferentially spaced apart locking teeth 590d of the end of the shear pin bushing 590. In this manner, the upper cam 598 is retained within the upper cone retainer 596 and torque loads may be transmitted between the upper cam and the shear pin bushing 590.

Referring to Figs. 25b and 25c, the upper cam 598 further includes a plurality of circumferentially spaced apart cam arms 598d that extend from the tubular base 598a in the longitudinal direction that mate with, receive, and are movably coupled to the cone mandrel 588. Each cam arm 598d includes an inner surface 598da that is an arcuate cylindrical segment, a first outer surface 598db that is an arcuate cylindrical segment, a second outer surface 598dc that is an arcuate conical segment, and a third outer surface 598dd that is an arcuate cylindrical segment. In an exemplary embodiment, each of the cam arms 598d are identical.

Referring to Figs. 24j, 25a, and 25d, a plurality of circumferentially spaced apart upper cone segments 600 are interleaved among the cam arms 598d of the upper cam 598. In an exemplary embodiment, each upper cone segment 600 includes a first outer surface 600a that defines a hinge groove 600b, a second outer surface 600c, a third outer surface 600d, a fourth outer surface 600e, a first inner surface 600f, a second inner surface 600g, a third inner surface 600h, and a fourth inner surface 600i. In an exemplary embodiment, the first outer surface 600a, the second outer surface 600c, the fourth outer surface 600e, the first inner surface 600f, the second inner surface 600g, and the fourth inner surface 600i are arcuate cylindrical segments. In an exemplary embodiment, the third outer surface 600d is an arcuate spherical segment.

In an exemplary embodiment, the third inner surface 600h is an arcuate conical segment. In an exemplary embodiment, each of the upper cone segments 600 are identical. In an exemplary embodiment, the hinge grooves 600b of the upper cone segments 600 receive and mate with the pivot point 596b of the upper cone retainer 596. In this manner, the upper cone segments 600 are pivotally coupled to the upper cone retainer 596.

Referring to Figs. 24j, 25a, and 25e, a plurality of circumferentially spaced apart lower cone segments 602 overlap with and are interleaved among the upper cone segments 600. In an exemplary embodiment, each lower cone segment 602 includes a first outer surface 602a that defines a hinge groove 602b, a second outer surface 602c, a third outer surface 602d, a fourth outer surface 602e, a first inner surface 602f, a second inner surface 602g, a third inner surface 602h, and a fourth inner surface 602i. In an exemplary embodiment, the first outer surface 602a, the second outer surface 602c, the fourth outer surface 602e, the first inner surface 602f, the second inner surface 602g, and the fourth inner surface 602i are arcuate cylindrical segments. In an exemplary embodiment, the third outer surface 602d is an arcuate spherical segment. In an exemplary embodiment, the third inner surface 602h is an arcuate conical segment. In an exemplary embodiment, each of the lower cone segments 602 are identical.

Referring to Figs. 24j, 25a, 25b, and 25f, a plurality of circumferentially spaced apart cam arms 604a that extend in the longitudinal direction from a tubular base 604b of a lower cam 604 overlap and are interleaved among the circumferentially spaced apart cam arms 598d of the upper cam 598 and mate with, receive, and are movably coupled to the cone mandrel 588. The tubular base 604b of the lower cam 604 mates with, receives, and is movably coupled to the cone mandrel 588 and includes an external flange 604c and a plurality of circumferentially spaced apart locking teeth 604d. Each cam arm 604a includes an inner surface 604aa that is an arcuate cylindrical segment, a first outer surface 604ab that is an arcuate cylindrical segment, a second outer surface 604ac that is an arcuate conical segment, and a third outer surface 604ad that is an arcuate cylindrical segment. In an exemplary embodiment, each of the cam arms 604a are identical.

An end of a lower cone retainer 606 includes an inner pivot point flange 606a that mates with and is received within the hinge grooves 602b of the lower cone segments

602. In this manner, the lower cone segments 602 are pivotally coupled to the lower cone retainer 606. The lower cone retainer 606 further includes an inner flange 606b that mates with and retains the external flange 604c of the lower cam 604. In this manner, the lower cam 604 is retained within the lower cone retainer 606.

The other end of the lower cone retainer 606 receives and is threadably coupled to an end of a release housing 608 that defines a radial passage 608a at another end and includes a plurality of circumferentially spaced apart locking teeth 608b at the end of the release housing for engaging the circumferentially spaced apart locking teeth 604d of the lower cam 604. In this manner, torque loads may be transmitted between the release housing 608 and the lower cam 604. An end of a lower mandrel 610 that defines a longitudinal passage 610a, an external radial mounting hole 610b, and radial passages 610c is received within, mates with, and is movably coupled to the other end of the release housing 608. A torsion locking pin 612 is mounted within and coupled to the external radial mounting hole 610b of the lower mandrel 610 and received within the radial passage 608a of the release housing 608. In this manner, longitudinal and torque loads may be transmitted between the release housing 608 and the lower mandrel 610.

An end of a locking dog retainer sleeve 614 that defines an inner annular recess 614a at one end and includes a plurality of circumferentially spaced apart locking teeth 614b at one end for engaging the locking teeth 604d of the lower cam 604 is received within and threadably coupled to an end of the lower mandrel 610. The locking dog retainer sleeve 614 is also positioned between and movably coupled to the release housing 608 and the cone mandrel 588. Locking dogs 616 are received within the inner annular recess 614a of the locking dog retainer sleeve 614 that releasably engage the locking dog grooves 588h provided in the exterior surface of the cone mandrel 588. In this manner, the locking dogs 616 releasably limit the longitudinal displacement of the lower cone segments 602, lower cam 604, and the lower cone retainer 606 relative to the cone mandrel 588.

A locking ring retainer 618 is received within and is threadably coupled to an end of the lower mandrel 610 that defines an inner annular recess 618a for retaining a resilient locking ring 620 within the lock ring groove 588d of the cone mandrel 588. The locking ring retainer 618 further mates with and is movably coupled to the cone mandrel 588. An end of an emergency release sleeve 622 that defines radial

passages 622a, an outer annular recess 622b, and a longitudinal passage 622c is received within and is threadably coupled to an end of the lower mandrel 610. The emergency release sleeve 622 is also received within, mates with, and slidably and sealingly engages an end of the cone mandrel 588.

An end of a pressure balance piston 624 is received within, mates with, and slidably and sealingly engages the end of the lower mandrel 610 and receives, mates with, and is threadably coupled to an end of the cone mandrel 588. The other end of the pressure balance piston 624 receives, mates with, and slidably and sealingly engages the emergency release sleeve 622.

An end of a bypass valve operating probe 626 that defines a longitudinal passage 626a is received within and is threadably coupled to another end of the lower mandrel 610. An end of an expansion cone mandrel 628 that defines radial passages 628a receives and is threadably coupled to the other end of the lower mandrel 610. A sealing sleeve expansion cone 630 is slidably coupled to the other end of the expansion cone mandrel 628 that includes an outer tapered expansion surface 630a. A guide 632 is releasably coupled to another end of the expansion cone mandrel 628 by a retaining collet 634.

An end of an expandable sealing sleeve 636 receives and is mounted on the sealing sleeve expansion cone 630 and the guide 632. The other end of the expandable sealing sleeve 636 receives and is threadably coupled to an end of a bypass valve body 638 that defines radial passages, 638a and 638b. An elastomeric coating 640 is coupled to the exterior of at least a portion of the expandable sealing sleeve 636. An end of a probe guide 642 that defines an inner annular recess 642a is received within and is threadably coupled to an end of the bypass valve body 638 and receives and mates with an end of the bypass valve operating probe 626.

A bypass valve 644 that defines a longitudinal passage 644a and radial passages, 644b and 644c, and includes a collet locking member 644d at one end for releasably engaging an end of the bypass valve operating probe 626 is received within, mates with, and slidably and sealingly engages the bypass valve body 638. An end of a lower mandrel 646 that defines a longitudinal passage 646a receives and is threadably coupled to an end of the bypass valve body 638.

An end of a dart guide sleeve 648 that defines a longitudinal passage 648a is received within and is coupled to an end of the bypass valve body 638 and the other

end of the dart guide sleeve 648 is received within and is coupled with the lower mandrel 646. An end of a differential piston 650 that includes an inner flange 650a at another end receives and is coupled to an end of the lower mandrel 646 by one or more shear pins 652. An end of a float valve assembly 654 including a float valve 654a, a valve guard 654b, and a guide nose 654c receives and is threadably coupled to an end of the lower mandrel 646. A plurality of circumferentially spaced apart locking dogs 656 are pivotally coupled to the inner flange 650a of the differential piston 650 and are further supported by an end of the float valve assembly 654.

As illustrated in Figs. 24a-24k, in an exemplary embodiment, during operation of the apparatus 400, the apparatus is initially positioned within a preexisting structure 700 such as, for example, a wellbore that traverses a subterranean formation. In several alternative embodiments, the wellbore 700 may have any inclination from vertical to horizontal. Furthermore, in several alternative embodiments, the wellbore 700 may also include one or more preexisting wellbore casings, or other well construction elements, coupled to the wellbore. During the positioning of the apparatus 400 within the wellbore 700, the casings, 468 and 470, are supported by the positive casing locking dog 464 and the torsional shear pins, 592a and 592b. In this manner, axial and torque loads may be transmitted between the casings, 468 and 470, and the tubular support member 402.

In an exemplary embodiment, as illustrated in Fig. 25h, prior to the assembly of the apparatus 400, the force of the spring 418 applies a sufficient downward longitudinal force to position the ends of the casing gripper locking dogs, 424a and 424b, between the outer annular recesses, 406d and 406e, of the gripper upper mandrel 406 thereby placing the bypass valve body 412 in a neutral position. In an exemplary embodiment, when the apparatus 400 is assembled by inserting the apparatus into the casing 468, the ends of the casing gripper locking dogs, 424a and 424b, impact the upper end of the casing 468 and are thereby displaced, along with the bypass valve body 412, upwardly relative to the gripper upper mandrel 406 until the ends of the casing gripper locking dogs pivot radially inwardly into engagement with the outer annular recess 406d of the gripper upper mandrel. In this manner, the bypass valve body 412 is positioned in an inactive position, as illustrated in Fig. 24a, that fluidicly decouples the casing gripper hydraulic ports, 406f and 406h. The upward displacement of the bypass valve body 412 relative to the gripper upper mandrel 406

further compresses the spring 418. The bypass valve body 412 is then maintained in the inactive position due to the placement of the casing gripper locking dogs, 424a and 424b, within the casing 468 thereby preventing the ends of the casing gripper locking dogs from pivoting radially outward out of engagement with the outer annular recess 406d.

Referring to Figs. 26a-26k, when the apparatus 400 is positioned at a desired predetermined position within the wellbore 700, a fluidic material 702 is injected into the apparatus through the passages 402a, 404a, 406a, 454a, 450a, 456a, 458a, 476a, 478a, 484a, 522a, 529a, 534a, 544a, 554a, 566a, 588a, 622c, 610a, 626a, 644a, and 646a and out of the apparatus through the float valve 654a. In this manner the proper operation of the passages 402a, 404a, 406a, 454a, 450a, 456a, 458a, 476a, 478a, 484a, 522a, 529a, 534a, 544a, 554a, 566a, 588a, 622c, 610a, 626a, 644a, and 646a and the float valve 654a may be tested. A dart 704 is then injected into the apparatus with the fluidic material 702 through the passages 402a, 404a, 406a, 454a, 450a, 456a, 458a, 476a, 478a, 484a, 522a, 529a, 534a, 544a, 554a, 566a, 588a, 622c, 610a, 626a, and 644a until the dart is positioned and seated in the passage 646a of the lower mandrel 646. As a result of the positioning of the dart 704 in the passage 646a of the lower mandrel 646, the passage of the lower mandrel is thereby closed.

The fluidic material 702 is then injected into the apparatus thereby increasing the operating pressure within the passages 402a, 404a, 406a, 454a, 450a, 456a, 458a, 476a, 478a, 484a, 522a, 529a, 534a, 544a, 554a, 566a, 588a, 622c, 610a, 626a, and 644a. Furthermore, the continued injection of the fluidic material 702 into the apparatus 400 also causes the fluidic material 702 to pass through the radial passages, 526b and 526c, 530b and 530c, and 536b and 536c, of the piston 526, 530, and 536, respectively, into an annular pressure chamber 706 defined between the actuator barrel 492 and the connector tube 529, an annular pressure chamber 708 defined between the actuator barrel 502 and the connector tube 534, and an annular pressure chamber 710 defined between the actuator barrel 512 and the connector tube 544.

The pressurization of the annular pressure chambers, 706, 708, and 710 then cause the pistons 526, 530, and 536 to be displaced upwardly relative to the casing 470. As a result, the connector tube 529, the connector tube 534, the connector tube 544, the threaded bushing 550, the lock nut 552, the tool joint adaptor 554, the sealing sleeve 558, the tool joint adaptor 560, the torsion plate 562, the upper bushing 564, the

cup mandrel 566, the thimble 568, the inner thimble 570, the packer cup 572, the backup ring 574, the spacer 576, the thimble 578, the inner thimble 580, the packer cup 582, the backup ring 584, the spacer 586, and the cone mandrel 588 are displaced upwardly relative to the casing 470, the shear pin bushing 590, the locking ring 594, the upper cone retainer 596, the upper cam 598, and the upper cone segments 600.

As a result, as illustrated in Figs. 26j, 27a, and 27b, the shear pin bushing 590, the locking ring 594, the upper cone retainer 596, the upper cam 598, and the upper cone segments 600 are displaced downwardly relative to the cone mandrel 588, the lower cone segments 602, and the lower cam 604 thereby driving the upper cone segments 600 onto and up the cam arms 604a of the lower cam 604, and driving the lower cone segments 602 onto and up the cam arms 598d of the upper cam 598. During the outward radial displacement of the upper and lower cone segments, 600 and 602, the upper and cone segments translate towards one another in the longitudinal direction and also pivot about the pivot points, 596b and 606a, of the upper and lower cone retainers, 596 and 606, respectively.

As a result, a segmented expansion cone is formed that includes a substantially continuous outer arcuate spherical surface provided by the axially aligned and interleaved upper and lower expansion cone segments, 600 and 602. Furthermore, the resilient locking ring 594 is relocated from the lock ring groove 588b to the lock ring groove 588c thereby releasably locking the positions of the shear pin bushing 590, the locking ring 594, the upper cone retainer 596, the upper cam 598, and the upper cone segments 600 relative to the cone mandrel 588.

Referring to Figs. 28a to 28j, the continued injection of the fluidic material 702 into the apparatus 400 continues to pressurize annular pressure chambers, 706, 708, and 710. As a result, an upward axial force is applied to the shear pin bushing 590 that causes the torsional shear pins, 592a and 592b, to be sheared thereby decoupling the wellbore casing 470 from the shear pin bushing 590 and permitting the pistons 526, 530, and 536 to be further displaced upwardly relative to the casing 470. The further upward displacement of the pistons 526, 530, and 536 in turn displaces the cone mandrel 588, the upper cam 598, the upper cone segments 600, the lower cone segments 602, and the lower cam 604 upwardly relative to the casing 470. As a result, the segmented expansion cone provided by the interleaved and axially aligned upper

and lower cone segments, 600 and 602, radially expands and plastically deforms a portion of the casing 470.

Referring to Figs. 29a-29m, during the continued injection of the fluidic material 702, the segmented expansion cone provided by the interleaved and axially aligned upper and lower cone segments, 600 and 602, will continue to be displaced upwardly relative to the casing 470 thereby continuing to radially expand and plastically deform the casing until the locking dogs 656 engage and push on the lower end of the casing 470. When the locking dogs 656 engage and push on the lower end of the casing 470, the locking dogs 656, the float valve assembly 654, the differential piston 650, the dart guide sleeve 648, the lower mandrel 646, the bypass valve 644, the elastomeric coating 640, the bypass valve body 638, the expandable sealing sleeve 636, the retaining collet 634, the guide 632, the sealing sleeve expansion cone 630, the expansion cone mandrel 628, the bypass valve operating probe 626, the pressure balance piston 624, the emergency release sleeve 622, the resilient locking ring 620, the locking ring retainer 618, the locking dogs 616, the locking dog retainer sleeve 614, the torsion locking pin 612, the lower mandrel 610, the release housing 608, the lower cone retainer 606, the lower cam 604, and the lower cone segments 602 are displaced downwardly in the longitudinal direction relative to the cone mandrel 588. As a result, the upper cam 598 and the upper cone segments 600 are moved out of axial alignment with the lower cone segments 602 and the lower cam 604 thereby collapsing the segmented expansion cone. Furthermore, the locking ring 620 is moved from the lock ring groove 588d to the lock ring groove 588e thereby releasably fixing the new position of the lower cone segments 602 and the lower cam 604.

In particular, as illustrated in Fig. 30a, when a downward tensile longitudinal force is initially applied to the lower mandrel 610 relative to cone mandrel 588, the lower mandrel, the locking dog retainer sleeve 614, and the locking ring retainer 618 are displaced downwardly relative to the cone mandrel 588 when the applied tensile force is sufficient to release the locking ring 620 from engagement with the lock ring groove 588d. As illustrated in Fig. 30b, if the applied tensile force is sufficient to release the locking ring 620 from engagement with the lock ring groove 588d, the lower mandrel 610, the locking dog retainer sleeve 614, and the locking ring retainer 618 are displaced downwardly relative to the cone mandrel 588 thereby displacing the annular recess 614a of the locking dog retainer sleeve downwardly relative to the locking dogs

616. As a result, the locking dogs 616 are released from engagement with the locking dog grooves 588h of the cone mandrel 588 thereby permitting the lower cone segments 602, the lower cam 604, and the lower cone retainer 606 to be displaced downwardly relative to the cone mandrel 588.

As illustrated in Fig. 30c, further downward displacement of the lower mandrel 610 then causes the torsion locking pin 612 to engage and displace the release housing 608 downwardly relative to the cone mandrel 588 thereby displacing the locking dogs 616, the lower cone retainer 606, the lower cam 604, and the lower cam segments 602 downwardly relative to the cone mandrel. As a result, the lower cone segments 602 and the lower cam 604 are displaced downwardly out of axial alignment with the upper cam 598 and the upper cam segments 600 thereby collapsing the segmented expansion cone. Furthermore, the downward displacement of the locking dog retainer sleeve 614 also displaced the locking ring retainer 618 and the locking ring 620 downwardly relative to the cone mandrel 588 thereby relocating the locking ring from the lock ring groove 588d to the lock ring groove 588e. In this manner, the now position of the lower cone segments 602 and the lower cam 604 are thereby releasably fixed relative to the cam mandrel 588 by the locking ring 620.

The operations of Figs. 30a-30c may be reversed, and the segmented expansion cone may again be expanded, by applying a upward compressive force to the lower mandrel 610. If the compressive force is sufficient, the locking ring 620 will be released from engagement with the lock ring groove 588e, thereby permitting the lower mandrel 610 and the locking dog retainer 614 to be displaced upwardly relative to the cone mandrel 588. As a result, the locking dog retainer 614 will engage and displace the locking dogs 616, the lower cam 604, the lower cone segments 602, the lower cone retainer 606, and the release housing 608 upwardly relative to the cone mandrel 588 thereby bringing the upper cam 598 and the upper cone segments 600 back into axial alignment with the lower cone segments 602 and the lower cam 604. As a result, the segmented expansion cone is once again expanded. Once the segmented cone has been fully expanded, the locking dogs 616 will once again be positioned in alignment with the locking dog grooves 588h of the cone mandrel 588 and will thereby once again engage the locking dog grooves. The continued upward displacement of the lower mandrel 610 relative to cone mandrel 588 will thereby also upwardly displace the locking dog retainer 614 upwardly relative to the cone mandrel thereby once again

capturing and restraining the locking dogs 616 within the annular recess 614a of the locking dog retainer. As a result, the new expansion position of the lower cone segments 602 and the lower cam 604 relative to the cone mandrel 588 will be releasably locked by the locking dogs 616. Furthermore, the locking ring 620 will also be relocated from engagement with the lock ring groove 588e to engagement with the lock ring groove 588d to thereby releasably lock the expanded segmented cone in the expanded position.

Referring to Figs. 31a-31n, the continued injection of the fluidic material 702 into the apparatus 400 continues to pressurize the piston chambers 706, 708, and 710 thereby further displacing the pistons upwardly 526, 530, and 536 upwardly relative to the support member 402. Because the engagement of the locking dogs 656 with the lower end of the casing 470 prevents float valve 654 from entering the casing, the continued upward displacement of the pistons 526, 530, and 536 relative to the support member 402 causes the bypass valve operating probe 626 to be displaced upwardly relative to the support member thereby disengaging the bypass valve operating probe from the probe guide 642, and also causes the sealing sleeve expansion cone 630 to be displaced upwardly relative to the expandable sealing sleeve 636 thereby radially expanding and plastically deforming the sealing sleeve 636 and the elastomeric coating 640 into sealing engagement with the interior surface of the lower end of the casing 470. As a result, the lower end of the casing 470 is fluidicly sealed by the combination of the sealing engagement of the sealing sleeve 636 and elastomeric coating 640 with the interior surface of the lower end of the casing and the positioning the dart 704 within the passage 646a of the lower mandrel 646.

Continued injection of the fluidic material 702 into the apparatus 400 continues to pressurize the piston chambers 706, 708, and 710 until the pistons 536, 530 and 536 are displaced upwardly relative to the casing 470 to their maximum upward position relative to the support member 402. As a result, the dart ball guide 524 impacts the positive casing lock mandrel 478 with sufficient force to shear the shear pins, 428a and 428b, thereby decoupling the positive casing lock mandrel 478 from the casing lock barrel adaptor 474. The positive casing lock mandrel 478 is then displaced upwardly relative to the support member 402 which in turn displaces the positive casing lock releasing mandrel 476 upwardly relative to the positive casing locking dogs 464. As a result, the internal flanges, 464a and 464b, of the positive casing locking dogs are

relocated into engagement with the annular recesses, 476c and 476d, respectively, of the positive casing lock releasing mandrel 476. The positive casing lock casing collar 466 is thereby released from engagement with the positive casing locking dogs 464 thereby releasing the casings 468 and 470 from engagement with the support member 402. As a result, the positions of the casings, 468 and 470, are no longer fixed relative to the support member 402.

Referring to Figs. 32a-32k, the injection of the fluidic material 702 is stopped and the support member 402 is then lowered into the wellbore 700 until the float valve assembly 654 impacts the bottom of the wellbore. The support member 402 is then further lowered into the wellbore 700, with the float valve assembly 654 resting on the bottom of the wellbore, until the bypass valve operating probe 626 impacts and displaces the bypass valve 644 downwardly relative to the bypass valve body 638 to fluidicly couple the passages, 638a and 644b, and the passages, 638b and 644c, and until sufficient upward compressive force has been applied to the lower mandrel 610 to re-expand the segmented expansion cone provided by the cone segments, 600 and 602. In an exemplary embodiment, the collet locking member 644d of the bypass valve 644 will also engage an end of the bypass valve operating probe 626.

In an exemplary embodiment, the support member 402 is lowered downwardly into the wellbore 700 such that sufficient upward compressive force is applied to the lower mandrel 610 to release the locking ring 620 from engagement with the lock ring groove 588e, thereby permitting the lower mandrel 610 and the locking dog retainer 614 to be displaced upwardly relative to the cone mandrel 588. As a result, the locking dog retainer 614 will engage and displace the locking dogs 616, the lower cam 604, the lower cone segments 602, the lower cone retainer 606, and the release housing 608 upwardly relative to the cone mandrel 588 thereby bringing the upper cam 598 and the upper cone segments 600 back into axial alignment with the lower cone segments 602 and the lower cam 604. As a result, the segmented expansion cone is once again expanded. Once the segmented cone has been fully expanded, the locking dogs 616 will once again be positioned in alignment with the locking dog grooves 588h of the cone mandrel 588 and will thereby once again engage the locking dog grooves. The continued upward displacement of the lower mandrel 610 relative to cone mandrel 588 will thereby also upwardly displace the locking dog retainer 614 upwardly relative to the cone mandrel thereby once again capturing and restraining the locking dogs 616 within

the annular recess 614a of the locking dog retainer. As a result, the new expansion position of the lower cone segments 602 and the lower cam 604 relative to the cone mandrel 588 will be releasably locked by the locking dogs 616. Furthermore, the locking ring 620 will also be relocated from engagement with the lock ring groove 588e to engagement with the lock ring groove 588d to thereby releasably lock the expanded segmented cone in the expanded position.

A hardenable fluidic sealing material 712 may then be injected into the apparatus 400 through the passages 402a, 404a, 406a, 454a, 450a, 456a, 458a, 476a, 478a, 522a, 526a, 529a, 530a, 534a, 536a, 544a, 554a, 566a, 588a, 622a, 610a, 626a, 638a, 638b, 644b, and 644c, and out of the apparatus through the circumferential gaps defined between the circumferentially spaced apart locking dogs 656 into the annulus between the casings 468 and 470 and the wellbore 700. In an exemplary embodiment, the hardenable fluidic sealing material 712 is a cement suitable for well construction. The hardenable fluidic sealing material 712 may then be allowed to cure before or after the further radial expansion and plastic deformation of the casings 468 and/or 470.

Referring to Figs. 33a-33p, after completing the injection of the fluidic material 712, the support member 402 is then lifted upwardly thereby displacing the bypass valve operating probe 626 and the bypass valve 644 upwardly to fluidicly decouple the passages, 638a and 644b and 638b and 644c, until the collet locking member 644d of the bypass valve is decoupled from the bypass valve operating probe. The support member 402 is then further lifted upwardly until the segmented expansion cone, provided by the interleaved and axially aligned cone segments, 600 and 602, impacts the transition between the expanded and unexpanded sections of the casing 470. A fluidic material 714 is then injected into the apparatus 400 through the passages 402a, 404a, 406a, 454a, 450a, 456a, 458a, 476a, 478a, 484a, 524a, 522a, 526a, 529a, 530a, 534a, 536a, 544a, 554a, 566a, 588a, 622c, 610a, and 626a thereby pressurizing the interior portion of the casing 470 below the packer cups, 572 and 582. In particular, the packer cups, 572 and 582, engage the interior surface of the casings 468 and/or 470 and thereby provide a dynamic movable fluidic seal. As a result, the pressure differential across the packer cups, 572 and 582, causes an upward tensile force that pulls the segmented expansion cone provided by the axially aligned and interleaved cone segments, 600 and 602, to be pulled upwardly out of the casings 468 and/or 407 by the packer cups thereby radially expanding and plastically deforming the casings.

Furthermore, the lack of a fluid tight seal between the cone segments, 572 and 582, and the casings 468 and/or 470 permits the fluidic material 714 to lubricate the interface between the cone segments and the casings during the radial expansion and plastic deformations of the casings by the cone segments. In an exemplary embodiment, during the radial expansion and plastic deformation of the wellbore casings 468 and/or 470, the support member 402 is lifted upwardly out of the wellbore 700. In several alternative embodiments, the casings 468 and/or 470 are radially expanded and plastically deformed into engagement with at least a portion of the interior surface of the wellbore 700.

Referring to Figs. 34a-34l, in an exemplary embodiment, a preexisting wellbore casing 716 is coupled to, or otherwise support by or within, the wellbore 700. In an exemplary embodiment, during the radial expansion and plastic deformation of the portion of the casing 468 and/or 470 that overlaps with the preexisting casing 716, during the continued injection of the fluidic material 714, the bypass valve body 412 is shifted downwardly relative to the gripper upper mandrel 406 thereby fluidicly coupling the casing gripper hydraulic ports, 406f and 406h. As a result, the interior passages, 428a and 440a, of the gripper bodies, 428 and 440, are pressurized thereby displacing the hydraulic slip pistons, 432a-432j and 442a-442j, radially outward into engagement with the interior surface of the preexisting wellbore casing 716. After the hydraulic slip pistons, 432a-432j and 442a-442j, engage the preexisting wellbore casing 716, the continued injection of the fluidic material 714 causes the segmented expansion cone including the axially aligned and interleaved cone segments, 600 and 602, to be pulled through the overlapping portions of the casings 468 and/or 470 and the preexisting wellbore casing by the upward displacement of the pistons, 526, 530, and 536, relative to the preexisting wellbore casing. In this manner, the overlapping portions of the casings 468 and/or 470 and the preexisting wellbore casing 716 are simultaneously radially expanded and plastically deformed by the upward displacement of the segmented expansion cone including the axially aligned and interleaved cone segments, 600 and 602. In several alternative embodiments, the hydraulic slip pistons, 432a-432j and 442a-442j, are displaced radially outward into engagement with the interior surface of the casings 468 and/or 470 and/or the preexisting wellbore casing 716.

In an exemplary embodiment, the bypass valve body 412 is shifted downwardly relative to the gripper upper mandrel 406 by lowering the casing gripper locking dogs, 424a and 424b, using the support member 402 to a position below the unexpanded portions of the casings 468 and/or 470 into the radially expanded and plastically deformed portions of the casings. The ends of the casing gripper locking dogs, 424a and 424b, may then pivot outwardly out of engagement with the outer annular recess 406d of the gripper upper mandrel 406 and then are displaced downwardly relative to the gripper upper mandrel, along with the bypass valve body 412, due to the downward longitudinal force provided by the compressed spring 418. As a result, the bypass valve body 412 is placed in the neutral position illustrated in Fig. 25h. The casing gripper locking dogs, 424a and 424b, are then displaced upwardly relative to the casing gripper upper mandrel 406 using the support member 402 thereby impacting the casing gripper locking dogs with the interior diameter of the unexpanded portion of the casings 468 and/or 470. As a result, the casing gripper locking dogs, 424a and 424b, are displaced downwardly, along with the bypass valve body 412. relative to the casing gripper upper mandrel 406 until the ends of the casing gripper locking dogs pivot radially inwardly into engagement with the outer annular recess 406e of the casing gripper upper mandrel thereby positioning the bypass valve body in an active position, as illustrated in Fig. 34a, in which the casing gripper hydraulic ports, 406f and 406h, are fluidicly coupled.

In an alternative embodiment, the bypass valve body 412 is shifted downwardly relative to the gripper upper mandrel 406 by raising the casing gripper locking dogs, 424a and 424b, to a position above the casing 468 using the support member 402 thereby permitting the ends of the casing gripper locking dogs to pivot radially outward out of engagement with the outer annular recess 406d of the gripper upper mandrel 406. The ends of the casing gripper locking dogs, 424a and 424b, are then displaced downwardly relative to the gripper upper mandrel, along with the bypass valve body 412, due to the downward longitudinal force provided by the compressed spring 418, into engagement with the outer annular recess 406e of the casing gripper upper mandrel thereby positioning the bypass valve body in an active position, as illustrated in Fig. 34a, in which the casing gripper hydraulic ports, 406f and 406h, are fluidicly coupled.

In an exemplary embodiment, the process of pulling the segmented expansion cone provided by pulling the interleaved and axially aligned cone segments, 600 and 602, upwardly through the overlapping portions of the casings 468 and/or 470 and the preexisting wellbore casing 716 is repeated by repeatedly stroking the pistons, 526, 530, and 536, upwardly by repeatedly a) injecting the fluidic material 714 to pressurize the apparatus 400 thereby displacing the segmented expansion cone upwardly, b) depressurizing the apparatus by halting the injection of the fluidic material, and then c) lifting the elements of the apparatus upwardly using the support member 402 in order to properly position the pistons for another upward stroke.

Referring to Figs. 35a-35l, in an exemplary embodiment, during the operation of the apparatus 400, the segmented expansion cone provided by the interleaved and axially aligned cone segments, 600 and 602, may be collapsed thereby moving the cone segments out of axial alignment by injecting a ball plug 718 into the apparatus using the injected fluidic material 714 through the passages 402a, 404a, 406a, 454a, 450a, 456a, 458a, 476a, 484a, 522a, 529a, 534a, 544a, 554a, 566a, and 588a into sealing engagement with the end of the emergency releasing sleeve 622. The continued injection of the fluidic material 714 following the sealing engagement of the ball plug 718 with the end of the emergency releasing sleeve 622 will apply a downward longitudinal tensile force to the lower mandrel 610. As a result, as illustrated and described above with reference to Fig. 30a, when the downward tensile longitudinal force is initially applied to the lower mandrel 610 relative to cone mandrel 588, the lower mandrel, the locking dog retainer sleeve 614, and the locking ring retainer 618 are displaced downwardly relative to the cone mandrel 588 when the applied tensile force is sufficient to release the locking ring 620 from engagement with the lock ring groove 588d. As illustrated in Fig. 30b, if the applied downward tensile longitudinal force is sufficient to release the locking ring 620 from engagement with the lock ring groove 588d, the lower mandrel 610, the locking dog retainer sleeve 614, and the locking ring retainer 618 are displaced downwardly relative to the cone mandrel 588 thereby displacing the annular recess 614a of the locking dog retainer sleeve downwardly relative to the locking dogs 616. As a result, the locking dogs 616 are released from engagement with the locking dog grooves 588h of the cone mandrel 588 thereby permitting the lower cone segments 602, the lower cam 604, and the lower cone retainer 606 to be displaced downwardly relative to the cone mandrel 588.

As illustrated in Fig. 30c, further downward displacement of the lower mandrel 610 then causes the torsion locking pin 612 to engage and displace the release housing 608 downwardly relative to the cone mandrel 588 thereby displacing the locking dogs 616, the lower cone retainer 606, the lower cam 604, and the lower cam segments 602 downwardly relative to the cone mandrel. As a result, the lower cone segments 602 and the lower cam 604 are displaced downwardly out of axial alignment with the upper cam 598 and the upper cam segments 600 thereby collapsing the segmented expansion cone. Furthermore, the downward displacement of the locking dog retainer sleeve 614 also displaced the locking ring retainer 618 and the locking ring 620 downwardly relative to the cone mandrel 588 thereby relocating the locking ring from the lock ring groove 588d to the lock ring groove 588e. In this manner, the now position of the lower cone segments 602 and the lower cam 604 are thereby releasably fixed relative to the cam mandrel 588 by the locking ring 620.

Referring now to Fig. 36a, an exemplary embodiment of the operation of the pressure balance piston 624 during an exemplary embodiment of the operation of the apparatus 400 will now be described. In particular, after the dart 704 is positioned and seated in the passage 646a of the lower mandrel 646, the operating pressure within the passage 622c will increase. As a result, the operating pressure within the passages 622a will increase thereby increasing the operating pressures within the passages, 588f and 588g, of the cone mandrel 588, and within an annulus 720 defined between the cone mandrel 588 and lower mandrel 610. The operating pressure within the annulus 720 acts upon an end face of the pressure balance piston 624 thereby applying a downward longitudinal force to the cone mandrel 588. As a result, the cone mandrel 588 and the locking dog retainer sleeve 614 could inadvertently be displaced away from each other in opposite directions during the pressurization of the interior passages of the apparatus 400 caused by the placement of the dart 704 in the passage 646a of the lower mandrel 646 thereby potentially collapsing the segmented expansion cone including the interleaved and axially aligned cone segments, 600 and 602. Thus, the pressure balance piston 624, in an exemplary embodiment, neutralizes the potential effects of the pressurization of the interior passages of the apparatus 400 caused by the placement of the dart 704 in the passage 646a of the lower mandrel 646.

Referring now to Fig. 36b, an exemplary embodiment of the operation of the pressure balance piston 624 during another exemplary embodiment of the operation of the apparatus 400 will now be described. In particular, during the placement of the ball 718 within the passage 622c of the releasing sleeve 622, the interior passages of the apparatus 400 upstream from the ball are pressurized. However, since the ball 718 blocks the passage 622c, the passage 622a is not pressurized. As a result, the pressure balance piston 624 does not apply a downward longitudinal force to the cone mandrel 588. As a result, the pressure balance piston 624 does not interfere with the collapse of the segmented expansion cone including the interleaved and axially aligned cone segments, 600 and 602, caused by the placement of the ball 718 within the mouth of the passage 622c of the release sleeve 622.

Although illustrative embodiments of the invention have been shown and described, a wide range of modification, changes and substitution is contemplated in the foregoing disclosure within the scope of the claims. Accordingly, it is appropriate that the invention be construed broadly and in a manner consistent with the scope of the claims.

11-45-05

Claims

1. A method of radially expanding and plastically deforming a tubular member, comprising:

positioning the tubular member within a preexisting structure;

radially expanding and plastically deforming a lower portion of the tubular member to form a bell section; and

radially expanding and plastically deforming a portion of the tubular member above the bell section,

wherein radially expanding and plastically deforming a lower portion of the tubular member to form a bell section comprises:

lowering an expansion device out of an end of the tubular member; and

pulling the expansion device through the end of the tubular member.

2. The method of claim 1, wherein positioning the tubular member within a preexisting structure comprises:

locking the tubular member to an expansion device.

3. The method of claim 2, wherein positioning the tubular member within a preexisting structure comprises:

unlocking the tubular member from an expansion device if the operating pressure within the preexisting structure exceeds a predetermined amount.

4. The method of claim 2, wherein positioning the tubular member within a preexisting structure comprises:

unlocking the tubular member from an expansion device if the position of an actuator coupled to the tubular member exceeds a predetermined amount.

5. The method of claim 1, wherein lowering an expansion device out of an end of the tubular member comprises:

lowering the expansion device out of the end of the tubular member; and

adjusting the size of the expansion device.

6. The method of claim 5, wherein the expansion device is adjustable to a plurality of sizes.

7. The method of claim 5, wherein the expansion device comprises a plurality of adjustable expansion devices.

8. The method of claim 7, wherein at least one of the adjustable expansion devices is adjustable to a plurality of sizes.

9. The method of claim 1, wherein pulling the expansion device through the end of the tubular member comprises:

gripping the tubular member; and

pulling an expansion device through an end of the tubular member.

10. The method of claim 1, wherein pulling the expansion device through the end of the tubular member comprises:

pulling the expansion device through the end of the tubular member using an actuator.

11. The method of claim 1, wherein radially expanding and plastically deforming a portion of the tubular member above the bell section comprises:

lowering an expansion device out of an end of the tubular member; and

pulling the expansion device through the end of the tubular member.

12. The method of claim 11, wherein lowering an expansion device out of an end of the tubular member comprises:

lowering the expansion device out of the end of the tubular member; and

adjusting the size of the expansion device.

13. The method of claim 12, wherein the expansion device is adjustable to a plurality of sizes.

14. The method of claim 12, wherein the expansion device comprises a plurality of adjustable expansion devices.

15. The method of claim 14, wherein at least one of the adjustable expansion devices is adjustable to a plurality of sizes.

16. The method of claim 11, wherein pulling the expansion device through the end of the tubular member comprises:

gripping the tubular member; and

pulling an expansion device through an end of the tubular member.

17. The method of claim 16, wherein pulling the expansion device through the end of the tubular member comprises:

pulling the expansion device through the end of the tubular member using an actuator.

18. The method of claim 11, wherein pulling the expansion device through the end of the tubular member comprises:

pulling the expansion device through the end of the tubular member using fluid pressure.

19. The method of claim 18, wherein pulling the expansion device through the end of the tubular member using fluid pressure comprises:

pressurizing an annulus within the tubular member above the expansion device.

20. The method of claim 1, wherein radially expanding and plastically deforming a portion of the tubular member above the bell section comprises:

fluidicly sealing an end of the tubular member; and

pulling the expansion device through the tubular member.

21. The method of claim 20, wherein the expansion device is adjustable.

22. The method of claim 21, wherein the expansion device is adjustable to a plurality of sizes.

23. The method of claim 20, wherein the expansion device comprises a plurality of adjustable expansion devices.

24. The method of claim 23, wherein at least one of the adjustable expansion devices is adjustable to a plurality of sizes.

25. The method of claim 20, wherein pulling the expansion device through the end of the tubular member comprises:

gripping the tubular member; and

pulling an expansion device through an end of the tubular member.

26. The method of claim 25, wherein pulling the expansion device through the end of the tubular member comprises:

pulling the expansion device through the end of the tubular member using an actuator.

27. The method of claim 20, wherein pulling the expansion device through the end of the tubular member comprises:

pulling the expansion device through the end of the tubular member using fluid pressure.

28. The method of claim 27, wherein pulling the expansion device through the end of the tubular member using fluid pressure comprises:

pressurizing an annulus within the tubular member above the expansion device.

29. The method of claim 1, wherein radially expanding and plastically deforming a portion of the tubular member above the bell section comprises:

overlapping the portion of the tubular member above the bell section with an end of a preexisting tubular member; and

pulling an expansion device through the overlapping portions of the tubular member and the preexisting tubular member.

30. The method of claim 29, wherein the expansion device is adjustable.

31. The method of claim 30, wherein the expansion device is adjustable to a plurality of sizes.

32. The method of claim 29, wherein the expansion device comprises a plurality of adjustable expansion devices.

33. The method of claim 32, wherein at least one of the adjustable expansion devices is adjustable to a plurality of sizes.

34. The method of claim 29, wherein pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member comprises:

gripping the tubular member; and

pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member.

35. The method of claim 34, wherein pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member comprises:

pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member using an actuator.

36. The method of claim 29, wherein pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member comprises:

pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member using fluid pressure.

37. The method of claim 36, wherein pulling the expansion device through the overlapping portions of the tubular member and the preexisting tubular member using fluid pressure comprises:

pressurizing an annulus within the tubular member above the expansion device.

38. The method of claim 1, further comprising:

injecting a hardenable fluidic sealing material into an annulus between the expandable tubular member and the preexisting structure.

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☑ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☑ GRAY SCALE DOCUMENTS
- ☑ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.
As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.